

# An XACML Attribute and Obligation Profile for Authorization Interoperability in Grids

*OSG*: Mine Altunay, Keith Chadwick, Gabriele Garzoglio (editor), Ted Hesselroth, John Hover, Tanya Levshina, Jay Packard, Valery Sergeev, Igor Sfiligoi, John Weigand  
*EGEE*: Yuri Demchenko, Oscar Koeroo (editor), Chad La Joie, Håkon Sagehaug  
*EGEE / INFN*: Vincenzo Ciaschini, Andrea Ferraro, Alberto Forti, Valerio Venturi  
*Globus*: Rachana Ananthakrishnan, Joe Bester, Frank Siebenlist  
*Condor*: Ian Alderman, Zach Miller

*May 16, 2008*  
*Document Version: v1.0*

## **Introduction**

Goal of the Authorization Interoperability activity is providing interoperability between middleware and authorization infrastructures. This is achieved by designing and implementing an authorization protocol common to OSG VO services, EGEE, Globus, and Condor. This protocol is based on the SAML profile of XACML v2.0 [XACML]. The C library that implements the profile is provided by the Globus Toolkit security group; the JAVA library by the SWITCH group of EGEE.

The authorization protocol is used by Policy Enforcement Points (PEP), i.e. resource gateways, to interact with Policy Decision Points (PDP), i.e. repository of authorization policies. For each access request, the PDP informs the PEP on whether access is granted or denied and the conditions to be enforced if access is granted. These conditions are expressed in the form of XACML Obligations and are the mechanism to restrict privileges at Grid resources.

## **How to interact with this document**

This document provides the specifications of Subject, Action, Resource, Environment, and Obligation attributes common to our groups. The attributes that we describe are commonly found and used in Grid scenarios; however, some of the attributes are implementation-specific and may be of significance only to a specific group, project, or software.

The authors acknowledge that some of the choices are not applicable to all authorization use cases. We do not exclude the possibility to update and extend these use cases, but, at this time, our focus is towards our production Grid infrastructures. The document focuses on X.509, VOMS, and POSIX-related credentials. Considerations on how to upgrade this document are discussed in the “Upgradeability” section.

## **Upgradeability**

This document describes a profile for authorization assertions targeting multiple resource types, such as computing elements, storage elements, and worker nodes. Such resources

are controlled by resource gateway software, or policy enforcement points (PEP e.g. Globus gatekeeper, SRM, etc.). According to the XACML model, the PEPs are responsible for contacting a policy decision point (PDP) at the site and enforcing its authorization decisions.

In this section we discuss how we recommend addressing the problems of resource gateway upgrades and of profile upgrades.

### **Resource Gateways Upgrades**

With the variety of PEPs discussed above and considering that the typical size of modern deployments consists of several hundreds nodes within a single administrative boundary, it is unavoidable that resource gateway software at a site will be upgraded at different times. This presents the following problem.

We foresee that the upgraded gateways will be able to enforce different / finer-grain authorization constraints, or “obligations”, from the site PDP, while the older gateways won’t be able to even understand such constraints. The XACML model, however, requires that a PEP must reject the authorization request, if it does not understand one of the obligations from the PDP. How can we allow a PDP to return the finer-grain obligations to the upgraded PEPs, which understand them, and to return old obligations to the old PEPs?

In this profile we provide the following solution. PEPs can communicate to the PDP the list of obligations that they understand, via the attribute SupportedObligations from the XACML environment request context. Such list can be considered by the PDP as advisory on the PEP capabilities, thus allowing the distinction between old and upgraded resource gateway software. If new PEP software is backward compatible, this mechanism allows resources and PDPs to be upgraded at different times. More details of this attribute are discussed in the Environment section.

### **Profile Upgrades**

We envision that this profile will evolve with time: new resources, actions, and subject attributes will be inevitably added to address new needs for access authorization. In order for the implementations of this profile to maintain their properties of interoperability within our group, we recommend the following practices:

- Attributes and obligations can be added to this profile, upon discussion within the group
- Attributes and obligation should not be removed from this profile, unless expressly agreed by the group. Removing attributes and obligations has potentially more disruptive consequences than adding new ones
- PDPs that implement the old profile, will ignore new attributes
- PDPs that implement the new profile, should not require new attributes in order to return old obligations. The SupportedObligations attribute from the PEP can guide the choice of a compatible set of obligations to return.
- PEPs that implement the old profile, should not be affected if the PDP is backward compatible and uses the SupportedObligations attribute from the PEP.

- PEPs that implement the new profile are recommended to maintain handlers for old obligations, in order to avoid authorization rejections due to unknown (old) obligations. Each PEP implementer will have to decide how backward compatible the PEP should be.

# Index

INTRODUCTION .....	1
HOW TO INTERACT WITH THIS DOCUMENT .....	1
UPGRADEABILITY .....	1
<i>Resource Gateways Upgrades</i> .....	2
<i>Profile Upgrades</i> .....	2
INDEX .....	4
NAMESPACE .....	6
<i>Attribute Namespace</i> .....	6
<i>URI choice: URN vs. URL</i> .....	6
XACML REQUEST .....	7
SUBJECT .....	7
<i>Namespace Prefix Expansion</i> .....	7
<i>Subject-x509-id</i> .....	7
<i>Subject-condor-canonical-name-id</i> .....	8
<i>Subject-x509-issuer</i> .....	8
<i>VO</i> .....	9
<i>VOMS-signing-subject</i> .....	9
<i>VOMS-signing-issuer</i> .....	9
<i>VOMS-FQAN</i> .....	10
<i>VOMS-Primary-FQAN</i> .....	10
OPTIONAL SUBJECT ATTRIBUTES .....	11
<i>Certificate-serial-number</i> .....	11
<i>CA-serial-number</i> .....	11
<i>VOMS-dns-port</i> .....	12
<i>Subject End-Entity X509v3 Certificate Policies OIDs</i> .....	12
<i>Certificate Chain</i> .....	13
ACTION .....	14
<i>Namespace Prefix Expansion</i> .....	14
<i>Queue: Action Type - Access a Job Queue</i> .....	14
<i>Execute-now: Action Type - Run Job Now</i> .....	15
<i>Access: Action Type - Access a Storage Resource</i> .....	15
<i>Resource Specification Language Attribute: rsl-string</i> .....	16
RESOURCE .....	16
<i>Namespace Prefix Expansion</i> .....	17
<i>CE: Resource Type - Computing Element</i> .....	17
<i>WN: Resource Type - Worker Node</i> .....	17
<i>SE: Resource Type - Storage Element</i> .....	18
<i>Host DNS name: dns-host-name</i> .....	19
<i>Resource X509 Service Certificate Subject: resource-x509-id</i> .....	19
<i>Resource X509 Service Certificate Issuer: resource-x509-issuer</i> .....	19
ENVIRONMENT .....	20
<i>Namespace prefix expansion</i> .....	20
<i>Supported Obligations</i> .....	20
<i>Pilot Job Invoker Identity</i> .....	21
XACML RESPONSE.....	22
OBLIGATIONS .....	22
<i>Namespace prefix expansion</i> .....	22
<i>UID GID</i> .....	23
<i>Multiple Secondary GIDs</i> .....	24
<i>Username</i> .....	24
<i>AFS Token</i> .....	25

<i>Path Restriction</i> .....	25
<i>Storage Priorities</i> .....	26
<i>Access Permission</i> .....	27
APPENDIX A: EXAMPLE RESPONSE / REQUEST MESSAGES AND CORRESPONDING XACML POLICIES .....	28
<i>A.1 Example of simple Request/Response and Policy</i> .....	28
<i>A.2 Example of Request/Response and Policy with simple negotiation between PEP and PDP about supported Obligations</i> .....	31
<i>A.3 Example of Request/Response and Policy for Pilot Job submitting to Worker Node</i> .....	35
APPENDIX B: LIST OF ATTRIBUTE AND OBLIGATION IDS INTRODUCED BY THIS PROFILE .....	38
<i>Subject Context</i> .....	38
<i>Action Context</i> .....	39
<i>Resource Context</i> .....	39
<i>Environment Context</i> .....	39
<i>Obligation Context and Attributes</i> .....	39
REFERENCES.....	40

## **Namespace**

The following sections discuss the Attribute Namespace for this profile.

### **Attribute Namespace**

This section describes the prefixes used for both URL and URN namespace styles for the authorization interoperability activities. For the short term, this group prefers a URL style namespace, even if the URN notation of specific standard attributes, like `urn:oasis:names:tc:xacml:1.0:resource:resource-id`, is used in these specifications.

Each attribute described in this document has an associated attribute name (attribute-id or obligation-id). This name needs to be concatenated with the following prefix when implementing this profile.

URL root prefix:       “`http://authz-interop.org/xacml`”

This namespace prefix is meant to be generic and not limited to the Grid-related use cases described in this document. People interested in using this namespace for use cases external to this document should contact David Groep, owner of the “`authz-interop.org`” namespace.

It is also considered that if the need arises to use a URN-style namespace identifier, the following prefix should be used:

URN root prefix:       “`x-urn:authz-interop:xacml`”

where “`x-urn`” indicates experimental namespace that doesn’t require registration with IANA (according to RFC2611).

### **URI choice: URN vs. URL**

In the previous section, we define a namespace for the authorization interoperability activities in both URN and URL styles. While this group prefers the URL style, we acknowledge that both styles present advantages and disadvantages.

A URN style namespace is preferred for reasons of compatibility with standards bodies like OASIS and IETF; however, using a URN requires the formal registration of the namespace with bodies like IANA. This approach is considered for the medium to long term for web-wide standardization of the Grid use cases described in this document. In the short term, should the need for an experimental URN namespace arise, we will use a URN defined with the ‘`x-`’ prefix, for “experimental namespace”, as described in the section above.

A URL style namespace is preferred because it does not require the registration of a namespace with any standardization body. The uniqueness of the namespace is derived by the uniqueness of the domain name. Moreover, additional services for XML schema resolution and location can be established at the registered domain. For example, both OGF and W3C support direct mapping and resolution of registered XML infoset schemas

into URLs. Infoset namespace is described in GFD.84, which also specifies the schema repository and service location as <http://schemas.ogf.org/>.

## **XACML Request**

The following sections define the authorization interoperability attributes for the XACML request message. It defines attributes for the subject, action, resource, and environment contexts.

### **Subject**

A PEP uses the subject contexts to declare for what entity the authorization decision is requested. The subject section in the request message contains multiple attributes. Each attribute is given a name or identifier, a datatype, and a value. The types are chosen from the available datatypes in the XML Schema [XMLSchema].

The subject attributes are used to determine an authorization decision, but not all attributes in the subject section need to play a role in the decision. All attributes must be present in the request, if the information is available when composing the request; PDPs consider attributes that are not present in the request as having a null value.

If subject-condor-canonical-name-id is present, the other attributes do not need to be present.

### **Namespace Prefix Expansion**

By concatenation with the URL and URN root-prefixes, the namespace prefix of subject attributes is expanded to the following prefix:

URL based namespace prefix:	<URL root prefix> + "/subject"
URN based namespace prefix:	<URN root prefix> + ":subject"

The namespace of each of the following attribute-ids is derived by concatenating this prefix with the given attribute-id name.

#### **Subject-x509-id**

This attribute holds the Distinguished Name (DN) of the user. This DN is the subject extracted from the user's certificate. The datatype of this attribute is string to accommodate the OpenSSL oneline representation of slash-separated Relative Distinguished Names.

We acknowledge that the most commonly used representation for this attribute is the X.500 datatype; however, we decide not to use it because the slash-separated representation is the defacto standard in our environment. Adopting an X.500 representation would require a transformation every time we created or parsed an XACML message.

*ID: subject-x509-id*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/subject-x509-id>  
XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/subject-x509-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>/O=dutchgrid/O=users/O=nikhef/CN=Oscar Koeroo</AttributeValue>
</Attribute>
```

### **Subject-condor-canonical-name-id**

This attribute holds the identity of a user in the condor system. The representation is similar to an email address and it is treated in this profile as of type String. This attribute is used in the context of the condor system to obtain, typically, a UID/GID or Username obligation. When this attribute is used, the other attributes do not need to be present. Vice versa, when this attribute is not used, the other attributes must be present, if known when composing the authorization request.

Requests containing a subject-condor-canonical-name-id should use the WN resource type and the “execute-now” action.

*ID: [subject-condor-canonical-name-id](#)*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/subject-condor-canonical-name-id>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/subject-condor-canonical-name-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>condor@fnal.gov</AttributeValue>
</Attribute>
```

### **Subject-x509-issuer**

This attribute holds the Distinguished Name (DN) of the CA that signed the user certificate. This DN is extracted from the user’s certificate. The datatype of this attribute is string, for the same reasons argued in the Subject-x509-id attribute.

*ID: [subject-x509-issuer](#)*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/subject-x509-issuer>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/subject-x509-issuer"
  DataType="http://www.w3.org/2001/XMLSchema#string">
```

```
<AttributeValue>/C=NL/O=NIKHEF/CN=NIKHEF medium-security certification auth
</AttributeValue>
</Attribute>
```

## **VO**

This attribute holds the name of the user VO. There are two methods for extracting the VO name from an Attribute Certificate (AC): (1) from the “VO” attribute of the VOMS AC; (2) from the left-most slash-separated portion of the FQAN attributes. This attribute contains the name extracted from the VO attribute of the AC (method 1).

*ID: vo*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/vo>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/vo"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>gin.ggf.org</AttributeValue>
</Attribute>
```

## **VOMS-signing-subject**

This attribute holds the DN of the VOMS service that signed the Attribute Certificate in the user credentials. It is extracted from the “issuer” attribute of the VOMS AC.

*ID: voms-signing-subject*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/voms-signing-subject>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/voms-signing-subject"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>
    /O=dutchgrid/O=hosts/OU=nikhef.nl/CN=kuiken.nikhef.nl
  </AttributeValue>
</Attribute>
```

## **VOMS-signing-issuer**

VOMS ACs are signed by a VOMS certificate. This attribute holds the DN of the CA that signed that VOMS certificate. This attribute can be extracted programmatically using the VOMS API and is not displayed in typical command line tools, like voms-proxy-info.

*ID: voms-signing-issuer*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/voms-signing-issuer>  
XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/voms-signing-issuer"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>/C=NL/O=NIKHEF/CN=NIKHEF medium-security certification auth
</AttributeValue>
</Attribute>
```

## **VOMS-FQAN**

This attribute holds one Fully Qualified Attribute Name from the VOMS Attribute Certificate in the user credentials. Because users typically belong to several groups, this attribute can be set many times to encode all FQAN in the AC.

*ID: voms-fqan*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/voms-fqan>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/voms-fqan"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>/gin.ggf.nl/APAC/Role=VO-Admin</AttributeValue>
</Attribute>
```

## **VOMS-Primary-FQAN**

This attribute holds the FQAN that conveys the user's primary group to the middleware. Such primary group is chosen by the user when interacting with VOMS.

In OSG, the middleware uses this information to map the user credentials to an account group or account pool and, eventually, to a specific local account. This account is used for job scheduling and accounting to associate computing and data storage activities to the user's VO group and group role.

In EGEE, for computing activities, the middleware uses the primary FQAN to map the user credentials to a primary Unix Group ID (GID). The primary GID is used in batch system scheduling and in the accounting system to associate computing and data storage activities to VO groups and roles. For data management activities, the primary FQAN can be used to select one specific storage pool out of all the available VO storage pools.

This attribute is extracted from the topmost FQAN attribute of the Attribute Certificate list of FQAN. Therefore, this FQAN is also available in one of the VOMS-FQAN attributes of the XACML request (see description above). This duplication guarantees that the order of the foremost FQAN is maintained and serves as a fast lookup of this information

*ID: voms-primary-fqan*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/voms-primary-fqan>  
XACML representation example:*

```
<Attribute  
  AttributeId="http://authz-interop.org/xacml/subject/primary-fqan"  
  DataType="http://www.w3.org/2001/XMLSchema#string">  
  <AttributeValue>/gin.ggf.nl/APAC/Role=VO-Admin</AttributeValue>  
</Attribute>
```

## **Optional Subject Attributes**

The following attributes are considered optional in this profile. They are discussed here to reserve the attribute names for a possible future use.

### **Certificate-serial-number**

This attribute holds the serial number of the user certificate. This attribute is of type integer. It is extracted from the user certificate.

This attribute can be used by a site to centrally black list a compromised certificate before the Certificate Revocation Lists from the CA are distributed to all gateways at a site.

This attribute is considered optional because the CA is responsible for conducting the investigation on whether to revoke a certificate. If the certificate needs to be revoked, sites expect that the CA takes immediate action, entering the certificate in the CRL.

*ID: certificate-serial-number*

*Type: integer*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/certificate-serial-number>*

*XACML representation example:*

```
<Attribute  
  AttributeId="http://authz-interop.org/xacml/subject/certificate-serial-number"  
  DataType="http://www.w3.org/2001/XMLSchema#integer">  
  <AttributeValue>28</AttributeValue>  
</Attribute>
```

### **CA-serial-number**

This attribute holds the CA's serial number used to sign the user certificate. The DN of such CA is the subject-issuer. The CA's serial number can be extracted from the CA certificate.

Sites can use this information to black list a compromised CA before the CA certificate is revoked. This attribute gives a finer-grain black listing capability than the CA DN. In fact, a CA can re-issue a new certificate, with a different serial number by design, but with the same DN as the compromised CA certificate. Blacklisting the DN would not allow to ban the compromised CA and accept the new CA, until the compromised CA certificate is in the Certificate Revocation List.

This attribute is considered optional because sites trust the CA to include the compromised CA certificate in the Certificate Revocation List before issuing a new CA certificate.

*ID: ca-serial-number*

*Type: integer*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/ca-serial-number>*

*XACML representation example:*

```
<Attribute
  AttributeId http://authz-interop.org/xacml/subject/ca-serial-number
  DataType="http://www.w3.org/2001/XMLSchema#integer">
  <AttributeValue>34</AttributeValue>
</Attribute>
```

### **VOMS-dns-port**

This attribute holds the DNS name of the host and the port number of the VOMS server that signed the VOMS ACs.

This attribute is considered optional because it is not currently used by any authorization middleware from our group.

*ID: voms-dns-port*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/voms-dns-port>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/subject/voms-dns-port"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>kuiken.nikhef.nl:15050</AttributeValue>
</Attribute>
```

### **Subject End-Entity X509v3 Certificate Policies OIDs**

This attribute holds active Certificate Policy OIDs for the certificate of the subject. These values are extracted from the user certificate. These values originate from the CA and give additional information about the certificate; for example, it allows distinguishing between user, host, service, and robot certificates. There can be multiple of these attributes set in one request.

This attribute is considered optional because it is not currently used by any authorization middleware from our group.

*ID: ca-policy-oid*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/subject/ca-policy-oid>*

*XACML representation example:*



```
CthL7N5PSFzpvEIVcBnQCuXRbANIOPf3fSOBEyKt49cJfCeZywCdPEJe/vzsat.jX
+zNfz+KBMtJ449neIekY+0xh8XR2s1VNgqjP0+5qkyBXb1QSLZn0k6015XAW1pKy
Ymp89wdk515cPJhTx65+Ier07yN7feotW6KtkxMLU/Fs77EmwoP.j+c0E2VAVAZFP
AZ8xiCNFGgpzPFHAtCngSjwjoU10Fd4v+4f1a18V41FcNt11hnaQZ6x832YyHDD09
1i791ebCBw2prcrwH0y5JEgdsWg8Qymbd+7dv7w13geb13a/Oq+0mMa/RiL3SKPx
dgfw33EuFg==
```

```
-----END CERTIFICATE-----</AttributeValue>
</Attribute>
```

## Action

The attributes in the Action context describe what action the subject wants to perform on the specified resource. In this profile, we have kept the accepted actions to a minimum. To do this, we have abstracted specific actions in single generic actions; for example, all interactions with the job queue of a CE resource is described by a single action named “queue”, which generalizes possible “queuing” actions like “submit-job”, “delete-job”, “query-job-status”, etc.. In addition, we use generalized actions for different types of resources, when possible: for example, the action “execute-now” applies to both CE and WN resources. We encourage these generalizations for future extensions to this profile.

We consider 3 types of actions. Their names are “queue”, “execute-now” and “access”, with prefix `<action-prefix>/action-type/`. A request defines a certain action by setting the value of the attribute name “action-id” to one of these 3 types of action names.

## Namespace Prefix Expansion

By concatenation with the URL and URN root-prefixes, the namespace prefix of action attributes (action-prefix) is expanded to the following prefix:

URL based namespace prefix: `<URL root prefix> + "/action"`  
URN based namespace prefix: `<URN root prefix> + ":action"`

## Queue: Action Type - Access a Job Queue

The “queue” action states that the subject requests authorization to interact with the job queue of the specified computing resource. The queue name, if available, can be extracted from the RSL string attribute of the action context.

This action is used in conjunction with the CE resource type, typically when requesting authorization to submit a job to the batch system queue controlled by a CE.

Note that action-id is a standardized attribute and it is left in URN notation.

*ID: action-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:action:action-id*

*ID Value: http://authz-interop.org/xacml/action/action-type/queue*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/action/action-type/queue*

*http://authz-interop.org/xacml/action/action-type/execute-now*

*http://authz-interop.org/xacml/action/action-type/access*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/action/action-type/queue
  </AttributeValue>
</Attribute>
```

### **Execute-now: Action Type - Run Job Now**

The “execute-now” action states that the subject requests authorization to execute immediately a job at the specified computing resource (e.g. for a typical CE, invoking the job-manager fork of a Globus gatekeeper).

Requests to a PDP containing a subject-condor-canonical-name-id should use the WN resource type and the “execute-now” action.

Note that action-id is a standardized attribute and it is left in URN notation.

*ID: action-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:action:action-id*

*ID Value: http://authz-interop.org/xacml/action/action-type/execute-now*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/action/action-type/queue*

*http://authz-interop.org/xacml/action/action-type/execute-now*

*http://authz-interop.org/xacml/action/action-type/access*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/action/action-type/execute-now
  </AttributeValue>
</Attribute>
```

### **Access: Action Type - Access a Storage Resource**

The “access” action states that the subject requests authorization to access a specified storage resource. The scope of the request is implementation-dependant: the request can regard access to a single file, a list of files, or a remote/local storage pool.

By design, this action generalizes finer-grain types of access, like read access, write access, file system administrative access, etc. Such fine-grain access control is delegated to the authorization layer of storage services. In fact, centralizing such control in the PDP is considered too costly in terms of performance. In addition, administrators typically are already comfortable with the authorization layers of their storage services and we see little benefit in proposing alternatives to such mechanisms.

Note that action-id is a standardized attribute and it is left in URN notation.

*ID: action-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:action:action-id*

*ID Value: http://authz-interop.org/xacml/action/action-type/access*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/action/action-type/queue*

*http://authz-interop.org/xacml/action/action-type/execute-now*

*http://authz-interop.org/xacml/action/action-type/access*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id "
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/action/action-type/access
  </AttributeValue>
</Attribute>
```

### **Resource Specification Language Attribute: rsl-string**

This attribute holds a string describing additional details of the action to be performed on the resource. This attribute is mainly thought to be used for actions performed on a CE resource, where such additional details can be described by a Globus Resource Specification Language [RSL] string. This string can hold information such as the name of the batch system queue targeted for job submission, the expected maximum running wall clock time for the job, etc.

*ID: rsl-string*

*Type: string*

*Full Attribute ID: http://authz-interop.org/xacml/action/rsl-string*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/action/rsl-string"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue> (jobtype='single')(maxtime=1100)(queue='hep')</AttributeValue>
</Attribute>
```

## **Resource**

The attributes in the Resource context describe the resource targeted for the authorization request. In this profile, we define only resources of particular interest to our community. We acknowledge that this is not a complete list and we encourage the extension of this section in future editions of this document.

In this context, we also define resource attributes useful for the authorization request, such as the DNS name of the machine hosting the gateway service to the resource and the X509 certificate information of that gateway service.

We consider 3 types of resources. Their names are “ce”, “wn” and “se”, with prefix *<resource-prefix>/resource-type/*. A request targets a certain resource by setting the value of the attribute name “resource-id” to one of these 3 types of resource name.

## Namespace Prefix Expansion

By concatenation with the URL and URN root-prefixes, the namespace prefix of resource attributes is expanded to the following prefix:

URL based namespace prefix: <URL root prefix> + "/resource "  
URN based namespace prefix: <URN root prefix> + ":resource"

## CE: Resource Type - Computing Element

The Computing Element resource manages the execution of jobs on underlying computing resources. The CE is responsible for interacting with the PDP before granting access to the job queuing system of its underlying computing cluster (“queue” action) or to the local machine execution environment (“execute-now” action).

Note that resource-id is a standardized attribute and it is left in URN notation.

*ID: resource-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:resource:resource-id*

*ID Value: http://authz-interop.org/xacml/resource/resource-type/ce*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/resource/resource-type/ce*

*http://authz-interop.org/xacml/resource/resource-type/se*

*http://authz-interop.org/xacml/resource/resource-type/wn*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/resource/resource-type/ce
  </AttributeValue>
</Attribute>
```

## WN: Resource Type - Worker Node

A Worker Node is a machine of a computing cluster. The Worker Node resource manages the execution of jobs on the local machine execution environment.

Job executions on WNs may or may not require an authorization decision initiated by a WN, depending on the job management model used. In a push-based job management model, WN authorization is not required: jobs are submitted to a CE, where the authorization request is issued, and then dispatched to the WN via the local batch system. In a pull-based job management model, WN is required: special jobs, referred to as pilot jobs, are dispatched to the WN using a push-based model; once pilot jobs start execution,

they pull a user job workload from a VO repository. To protect the execution environment, the WN issues an authorization request for the user workload; if granted, the workload is executed with the privileges locally assigned to that user. The authorization request initiated by the WN must use the action “execute-now”.

Requests to a PDP containing a subject-condor-canonical-name-id should use the WN resource type and the “execute-now” action.

Note that resource-id is a standardized attribute and it is left in URN notation.

*ID: resource-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:resource:resource-id*

*ID Value: http://authz-interop.org/xacml/resource/resource-type/wn*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/resource/resource-type/ce*

*http://authz-interop.org/xacml/resource/resource-type/se*

*http://authz-interop.org/xacml/resource/resource-type/wn*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/resource/resource-type/wn
  </AttributeValue>
</Attribute>
```

## **SE: Resource Type - Storage Element**

The Storage Element resource manages access to files and storage pools. Authorization requests to storage elements must use the action “access”.

Note that resource-id is a standardized attribute and it is left in URN notation.

*ID: resource-id*

*Type: string*

*Full Attribute ID: urn:oasis:names:tc:xacml:1.0:resource:resource-id*

*ID Value: http://authz-interop.org/xacml/resource/resource-type/se*

*Enumeration of possible values:*

*http://authz-interop.org/xacml/resource/resource-type/ce*

*http://authz-interop.org/xacml/resource/resource-type/se*

*http://authz-interop.org/xacml/resource/resource-type/wn*

*XACML representation example:*

```
<Attribute
  AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/resource/resource-type/se
  </AttributeValue>
</Attribute>
```

### **Host DNS name: dns-host-name**

This attribute specifies the fully qualified domain name of the machine hosting the gateway to the specified resource. Examples of such gateway include a Globus Gatekeeper, for the CE; SRM, for the SE; gLExec, for the WN.

This attribute is of type string.

*ID: dns-host-name*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/resource/dns-host-name>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/resource/dns-host-name"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>ce03.nikhef.nl</AttributeValue>
</Attribute>
```

### **Resource X509 Service Certificate Subject: resource-x509-id**

This attribute specifies the X509 subject of the service certificate that defines the identity of the resource gateway. This certificate is typically the host certificate of the machine hosting the gateway, but it can be a generic service certificate. If the information of this service certificate is available to the PEP authorization environment, this information must be included in the request.

This attribute is of type string, instead of X.500, for the same reasons discussed in the subject-x509-id attribute section.

*ID: resource-x509-id*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/resource/resource-x509-id>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/resource/resource-x509-id"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>/DC=org/DC=doegrids/OU=Services/CN=my.host.domain</AttributeValue>
</Attribute>
```

### **Resource X509 Service Certificate Issuer: resource-x509-issuer**

This attribute specifies the X509 issuer of the service certificate that defines the identity of the resource gateway. This attribute identifies the CA that signed the service certificate for the resource gateway. If the information of this service certificate is available to the PEP authorization environment, this information must be included in the request.

This attribute is of type string, instead of X.500, for the same reasons discussed in the subject-x509-id attribute section.

*ID: resource-x509-issuer*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/resource/resource-x509-issuer>*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/resource/resource-x509-issuer"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>/DC=org/DC=DOEGrids/OU=Certificate Authorities/CN=DOEGrids CA 1
  </AttributeValue>
</Attribute>
```

## **Environment**

The attributes in the Environment context convey additional parameters in the authorization request of the subject to perform an action on the specified resource. These additional parameters instruct the PDP on what obligations the PEP supports or convey information about the pilot job identity in case of authorization requests initiated by a WN.

### **Namespace prefix expansion**

By concatenation with the URL and URN root-prefixes, the namespace prefix of environment attributes is expanded to the following prefix:

URL based namespace prefix:      <URL root prefix> + "/environment"  
URN based namespace prefix:      <URN root prefix> + ":environment"

### **Supported Obligations**

PDPs encapsulate in obligation structures the set of constraints that a PEP must be able to satisfy before granting access to resources. Obligations are identified by an obligation id, which typically PEPs associate to obligation handler code. According to the XACML specifications, even if only one obligation cannot be satisfied by the PEP, the authorization must be denied. A PEP may not be able to satisfy an obligation because it does not know how to act upon it i.e. it does not have an appropriate handler for a certain obligation-id. Such situation may occur especially during upgrades of PDP servers, potentially resulting in PEP receiving new and unknown obligations, thus having to reject all authorization requests.

In order to mitigate such problem, this profile allows for a PEP to specify the list of known obligations via the XACML environment context. A PDP can take such list under advisement and deal with a version compatibility problem by returning a set of obligations appropriate for the PEP. On the other hand, it should be noted that a PDP can elect to ignore the list of supported obligations and still be compliant with this profile.

*The example below shows how a PEP uses the XACML environment context to communicate the list of obligations supported to a PDP.*

*ID: pep-oblig-supported*

*Type: string*

*Full Attribute ID: <http://authz-interop.org/xacml/environment/pep-oblig-supported>*

*ID Value: a valid obligation ID (see Obligations section)*

*Enumeration of possible values:*

*<http://authz-interop.org/xacml/obligation/uidgid>*

*<http://authz-interop.org/xacml/obligation/secondary-gids>*

*<http://authz-interop.org/xacml/obligation/username>*

*<http://authz-interop.org/xacml/obligation/afs-token>*

*<http://authz-interop.org/xacml/obligation/root-and-home-paths>*

*<http://authz-interop.org/xacml/obligation/storage-access-priority>*

*<http://authz-interop.org/xacml/obligation/access-permissions>*

*Notes: This attribute may appear multiple times, each time with a different value (as many times as supported obligations)*

*XACML representation example:*

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-supported"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/obligation/uidgid
  </AttributeValue>
</Attribute>
```

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-supported"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/obligation/secondary-gids
  </AttributeValue>
</Attribute>
```

```
<Attribute
  AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-supported"
  DataType="http://www.w3.org/2001/XMLSchema#string">
  <AttributeValue>http://authz-interop.org/xacml/obligation/username
  </AttributeValue>
</Attribute>
```

## **Pilot Job Invoker Identity**

The pull-based job management model can be summarized as follows. Special jobs, named “pilot” jobs, are submitted to Computing Elements. These jobs are authorized by the CE to access computing resources and are eventually dispatched to Worker Nodes via the local batch system. Once one such job runs at a Worker Node, it pulls a user workload from a VO repository. Such workload needs to be executed with the privileges of the user, not the privileges of the pilot. The WN can request authorization for the user to access the local WN execution environment and, if granted, execute the job under user privileges.

In this scenario, the authorization request conveys user identity information in the subject context, WN information (typically WN host certificate) in the resource context, and pilot job identity information in the environment context. Such information is important to enforce various policies on pilot job scenarios. An example of such a policy states that user access to the WN execution environment should be granted only if the pilot job belongs to the same VO of the user. With the information provided in this profile, such policy can be expressed and enforced.

The pilot job identity is expressed as a set of flat attributes in the environment context. All attributes specified in the subject context must be defined for the pilot identity in the environment context. Pilot attributes have the same attribute id of the subject attributes with different namespace:

<URL root prefix> + "/environment" + "/pilot-job"

Attributes that define the user identity in the subject context have the same meaning of the attributes that define the pilot identity in the environment context.

Authorization requests for an action "execute-now" on a resource "WN" must have pilot job identity information, unless the request contains a subject-condor-canonical-name-id attribute.

For a full list of attributes see the environment section in "Appendix B: List of Attribute and Obligation IDs introduced by this profile".

## ***XACML Response***

The following section defines the authorization interoperability attributes for the XACML response message. It defines obligations and attributes for the obligations context.

### ***Obligations***

The following is a list of obligations common to the AuthZ Interoperability group. Each obligation has an ID, a list of attributes, corresponding types, and a stakeholder (EGEE, VO Services project, ...). The types are chosen from the available datatypes in the XML Schema [XMLSchema]. This document also captures if an obligation requires the presence of another to make sense in our use cases. These dependencies will not be captured in a structured way in the protocol. It is up to the PEP that receives the message to validate these dependencies.

The combination of attributes in each of the described obligations is tuned to the use cases that are common to Grid systems. Attributes that cannot be useful separately are bound together in one obligation. Other attributes are split in different obligations because they can be combined in a response that is use case-dependent.

### **Namespace prefix expansion**

By concatenation with the URL and URN root-prefixes, the namespace prefix of obligations is expanded to the following prefix:

URL based namespace prefix: <URL root prefix> + “/obligation”  
URN based namespace prefix: <URN root prefix> + “:obligation”

The namespace prefix of attributes is expanded to the following prefix:

URL based namespace prefix: <URL root prefix> + “/attribute”  
URN based namespace prefix: <URN root prefix> + “:attribute”

## UID GID

This obligation requires that the resource gateway (PEP) creates an execution environment for the user with a specific Unix ID (UID) and Group ID (GID). If this obligation is received together with the username obligation, the two must be consistent i.e. the UID attribute from the uidgid obligation must be mapped to the given UNIX username and vice versa. If this is NOT the case, the authorization MUST be denied.

*ID:* uidgid

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/uidgid>

*Attributes:*

- *ID:* posix-uid  
*Description:* Unix User ID local to the PEP  
*Type:* integer  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/posix-uid>
- *ID:* posix-gid  
*Description:* Unix Group ID local to the PEP  
*Type:* integer  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/posix-gid>

*Stakeholder:* Common

*Must be consistent with:* Username

*XACML representation example:*

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/uidgid"
FulfillOn="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/posix-uid"
    DataType="http://www.w3.org/2001/XMLSchema#integer">
    7160
  </AttributeAssignment>
```

```
<AttributeAssignment
  AttributeId="http://authz-interop.org/xacml/attribute/posix-gid"
  DataType="http://www.w3.org/2001/XMLSchema#integer">
  1530
```

```
</AttributeAssignment>
</Obligation>
```

## Multiple Secondary GIDs

This obligation requires that the PEP sets secondary Unix Group IDs when creating the execution environment. The list of GIDs may be empty. This obligation is typically used in conjunction with UIDGID. The main use case for this obligation is to take full advantage of the Unix file permissions. This is needed to facilitate fine-grain access to specific storage areas.

*ID:* secondary-gids

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/secondary-gids>

*Attributes:*

- *ID:* posix-gid  
*Description:* Unix Group ID local to the PEP  
*Type:* integer  
*Notes:* this attribute can appear multiple times within this obligation  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/posix-gid>

*Stakeholder:* EGEE

*Needs obligation(s):* uidgid

*XACML representation example:*

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/secondary-gids"
Fulfillion="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/posix-gid"
    DataType="http://www.w3.org/2001/XMLSchema#integer">
    1531
  </AttributeAssignment>
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/posix-gid"
    DataType="http://www.w3.org/2001/XMLSchema#integer">
    1530
  </AttributeAssignment>
</Obligation>
```

## Username

This obligation requires that the PEP sets the UNIX username, passed as a string, for the execution environment. If this obligation is received together with the uidgid obligation, the two must be consistent i.e. the UID attribute from the UIDGID obligation must be mapped to the given UNIX username and vice versa. If this is not the case, the authorization MUST be denied.

*ID:* username

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/username>

*Attributes:*

- **ID:** *username*  
**Description:** Unix username or account name local to the PEP.  
**Type:** *string*  
**Full Attribute ID:** *http://authz-interop.org/xacml/attribute/username*

**Stakeholder:** VO Services Project

**Must be consistent with:** *uidgid*

**XACML representation example:**

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/username"
  Fulfillion="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/username"
    DataType="http://www.w3.org/2001/XMLSchema#string">
    garzoglio
  </AttributeAssignment>
</Obligation>
```

## AFS Token

This obligation requires that the PEP sets the AFS token passed from the Policy Decision Point via the obligation. When enforcing this obligation, the PEP obligation handler must check that the response message was transmitted with privacy and integrity. The authorization request should be rejected otherwise.

**ID:** *afs-token*

**Full Obligation ID:** *http://authz-interop.org/xacml/obligation/afs-token*

**Attributes:**

- **ID:** *afs-token*  
**Description:** AFS Token passed as a base64Binary type.  
**Type:** *base64Binary*  
**Full Attribute ID:** *http://authz-interop.org/xacml/attribute/afs-token*

**Stakeholder:** EGEE

**Needs obligation(s):** *uidgid*

**XACML representation example:**

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/afs-token"
  Fulfillion="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/afs-token"
    DataType="http://www.w3.org/2001/XMLSchema#base64Binary">
    aWtoZWYxFTATBgNVBAMTDE9zY2FyIEtVZXJvbzE0MwGA1UEAxMFcHJveHkwXDAN
    BgkqhkiG9w0BAQEFAANLADBIAGEAsIEsIXp1WQeL3X52VTvmT1a2XTP5DuCgov6w
    dhKWdYL/KPA/wj12HXBNvF/1Z1+09TZPJC/IDn.jnMPxp3bzv0wIDAQABoxIwEDAO
  </AttributeAssignment>
</Obligation>
```

## Path Restriction

This obligation requires that the PEP restricts access to the file system from the execution environment. In particular, it defines a sub-tree of the file system (RootPath) that should

be the “root” mount point of the execution environment (i.e. ‘/’) and it defines the path to the user’s home directory (HomeDir), as a subpath of the RootPath. This obligation is mostly used to control access privileges to storage elements and it is typically used in conjunction with UIDGID or Username.

*ID:* root-and-home-paths

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/root-and-home-paths>

*Attributes:*

- *ID:* rootpath  
*Description:* this parameter defines a sub-tree of the whole file system available at the PEP. The PEP should mount this sub-tree as the “root” mount point (‘/’) of the execution environment. This is an absolute path.  
*Type:* string  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/rootpath>
- *ID:* homepath  
*Description:* this parameter defines the path to home areas of the user accessing the PEP. This is a path relative to rootpath.  
*Type:* string  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/homepath>

*Stakeholder:* VO Services Project

*Needs obligation(s):* uidgid or username

*XACML representation example:*

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/root-and-home-
paths" FulfillOn="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/rootpath"
    DataType="http://www.w3.org/2001/XMLSchema#string">
    /pnfs/myvo/
  </AttributeAssignment>

  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/homepath"
    DataType="http://www.w3.org/2001/XMLSchema#string">
    <!-- Set the home path to /pnfs/myvo/home/garzoglio >
    home/garzoglio/
  </AttributeAssignment>
</Obligation>
```

## Storage Priorities

This obligation requires that the PEP provides access to storage resources with a priority indicated by the integer parameter passed via the obligation. The higher the integer value, the higher the priority. A priority is related to the position of the request in the data request queue. This obligation is typically used in conjunction with UIDGID or Username.

*ID:* storage-access-priority

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/storage-access-priority>  
*Attributes:*

- *ID:* *storage-priority*  
*Description:* an integer number that defines the priority to access storage resources.  
*Type:* integer  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/storage-priority>

*Stakeholder:* VO Services Project

*Needs obligation(s):* *uidgid or username*

*XACML representation example:*

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/storage-access-
priority" FulfillOn="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/storage-priority"
    DataType="http://www.w3.org/2001/XMLSchema#integer">
    10
  </AttributeAssignment>
</Obligation>
```

## **Access Permission**

This obligation requires that the PEP provide access to the storage resources in read-only or read-write modes. This obligation is typically used in conjunction with UIDGID or Username. Further finer-grain restrictions can be applied as POSIX permissions by the storage service when accessing individual files.

*ID:* *access-permissions*

*Full Obligation ID:* <http://authz-interop.org/xacml/obligation/access-permissions>

*Attributes:*

- *ID:* *access-permissions*  
*Description:* a string that represent the access permission to a file that is requested. This attribute can have values “read-only” or “read-write”.  
*Type:* string  
*Full Attribute ID:* <http://authz-interop.org/xacml/attribute/access-permissions>

*Stakeholder:* VO Services Project

*Needs obligation(s):* *uidgid or username*

*XACML representation example:*

```
<Obligation ObligationId="http://authz-interop.org/xacml/obligation/access-
permissions" FulfillOn="Permit">
  <AttributeAssignment
    AttributeId="http://authz-interop.org/xacml/attribute/access-permissions"
    DataType="http://www.w3.org/2001/XMLSchema#string ">
    read-only
  </AttributeAssignment>
</Obligation>
```

## Appendix A: Example Response / Request messages and corresponding XACML Policies

### A.1 Example of simple Request/Response and Policy

a) Simple Request message that contains information about requesting Subject, Resource, Action

```
[ 1] <Request
[ 2]     xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
[ 3]     xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
[ 4]     xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os
[ 5]         access_control-xacml-2.0-context-schema-os.xsd">
[ 6]     <!-- Example - Request: Simple Request-Policy-Response -->
[ 7]     <Subject>
[ 8]         <Attribute
[ 9]             AttributeId="http://authz-interop.org/xacml/subject/subject-x509-id"
[10]             DataType="http://www.w3.org/2001/XMLSchema#string">
[11]             <AttributeValue>/O=dutchgrid/O=users/O=nikhef/CN=Wim
Huizinga</AttributeValue>
[12]         </Attribute>
[13]         <Attribute
[14]             AttributeId="http://authz-interop.org/xacml/subject/subject-x509-issuer"
[15]             DataType="http://www.w3.org/2001/XMLSchema#string">
[16]             <AttributeValue>/C=NL/O=NIKHEF/CN=NIKHEF medium-security certification
auth</AttributeValue>
[17]         </Attribute>
[18]         <Attribute
[19]             AttributeId="http://authz-interop.org/xacml/subject/vo"
[20]             DataType="http://www.w3.org/2001/XMLSchema#string">
[21]             <AttributeValue>gin.ggf.nl</AttributeValue>
[22]         </Attribute>
[23]         <Attribute
[24]             AttributeId="http://authz-interop.org/xacml/subject/voms-primary-fqan"
[25]             DataType="http://www.w3.org/2001/XMLSchema#string">
[26]             <AttributeValue>/gin.ggf.nl/APAC/Role=Researcher</AttributeValue>
[27]         </Attribute>
[28]     </Subject>
[29]     <Resource>
[30]         <Attribute
[31]             AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
[32]             DataType="http://www.w3.org/2001/XMLSchema#anyURI">
[33]             <AttributeValue>http://authz-interop.org/xacml/resource/resource-
type/se</AttributeValue>
[34]         </Attribute>
[35]     </Resource>
[36]     <Action>
[37]         <Attribute
[38]             AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
[39]             DataType="http://www.w3.org/2001/XMLSchema#string">
[40]             <AttributeValue>http://authz-interop.org/xacml/action/action-
type/access</AttributeValue>
[41]         </Attribute>
[42]     </Action>
[43] </Environment/>
```

```
[ 44 ] </Request>
```

b) Response message with returned obligations in lines [53-58] to map user identity to returned UID and GID under which the user task/request will be executed.

```
[ 45 ] <?xml version="1.0" encoding="UTF-8"?>
[ 46 ] <Response xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xmlns:xacml="urn:oasis:names:tc:xacml:2.0:policy:schema:os"
[ 47 ]   xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os access_control-
      xacml-2.0-context-schema-os.xsd">
[ 48 ]     <Result ResourceId=" http://authz-interop.org/xacml/resource/resource-type/se">
[ 49 ]       <Decision>Permit</Decision>
[ 50 ]       <Status>
[ 51 ]         <StatusCode Value="urn:oasis:names:tc:xacml:1.0:status:ok"/>
[ 52 ]       </Status>
[ 53 ]       <xacml:Obligations>
[ 54 ]         <xacml:Obligation ObligationId="http://authz-
      interop.org/xacml/obligation/uidgid" FulfillOn="Permit">
[ 55 ]           <xacml:AttributeAssignment AttributeId="http://authz-
      interop.org/xacml/attribute/posix-uid"
      DataType="http://www.w3.org/2001/XMLSchema#integer">2501</xacml:AttributeAssignment
      >
[ 56 ]           <xacml:AttributeAssignment AttributeId="http://authz-
      interop.org/xacml/attribute/posix-gid"
      DataType="http://www.w3.org/2001/XMLSchema#integer">2101</xacml:AttributeAssignment
      >
[ 57 ]         </xacml:Obligation>
[ 58 ]       </xacml:Obligations>
[ 59 ]     </Result>
[ 60 ] </Response>
```

c) Example policy with obligations in lines [113-118].

- Policy Target in lines [71-90] provides conditions by which policy is selected based on information in the Request message: Subject VO and Resource
- Rule Target in lines [95-104] specifies action for which the rule is applied.
- Condition expression in lines [106-110] uses bag-function to specify that any of the Subject attributes with AttributeId=".../voms-fqan" should match value "/gin.ggf.nl/APAC/Role=Researcher"

e

```
[ 61 ] <?xml version="1.0" encoding="UTF-8"?>
[ 62 ] <Policy xmlns="urn:oasis:names:tc:xacml:2.0:policy:schema:os" xmlns:xacml-
      context="urn:oasis:names:tc:xacml:2.0:context:schema:os"
      xmlns:md="http://www.medico.com/schemas/record"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:policy:schema:os
[ 63 ]   access_control-xacml-2.0-policy-schema-os.xsd" PolicyId="http://authz-
      interop.org/xacml/example/example822/policy"
      RuleCombiningAlgId="urn:oasis:names:tc:xacml:1.0:rule-combining-algorithm:deny-
      overrides">
[ 64 ]   <Description>
[ 65 ]     Example 822 - Policy: Request: Simple Request-Policy-Response
[ 66 ]   </Description>
[ 67 ]   <PolicyDefaults>
[ 68 ]     <XPathVersion>http://www.w3.org/TR/1999/Rec-xpath-19991116</XPathVersion>
[ 69 ]   </PolicyDefaults>
[ 70 ]   <Target>
```

```

[71]         <Subjects>
[72]             <Subject>
[73]                 <SubjectMatch
[74] MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[75]                     <AttributeValue
[76]                         DataType="http://www.w3.org/2001/XMLSchema#string">
[77]                             gin.ggf.nl</AttributeValue>
[78]                                 <SubjectAttributeDesignator
[79]                                     SubjectCategory="urn:oasis:names:tc:xacml:1.0:subject-category:access-subject"
[80]                                     AttributeId="http://authz-interop.org/xacml/subject/vo"
[81]                                     DataType="http://www.w3.org/2001/XMLSchema#string"/>
[82]                                         </SubjectMatch>
[83]                                             </Subject>
[84] </Subjects>
[85] <Resources>
[86]     <Resource>
[87]         <ResourceMatch
[88] MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[89]             <AttributeValue
[90]                 DataType="http://www.w3.org/2001/XMLSchema#URI">http://authz-
[91] interop.org/xacml/resource/resource-type/se
[92]             </AttributeValue>
[93]                 <ResourceAttributeDesignator
[94]                     AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
[95]                     DataType="http://www.w3.org/2001/XMLSchema#URI"/>
[96]                         </ResourceMatch>
[97]                             </Resource>
[98] </Resources>
[99] </Target>
[100] <Rule RuleId="http://authz-interop.org/xacml/example/example822/policy/rule01"
[101] Effect="Permit">
[102]     <Description>
[103]         User with role "/gin.ggf.nl/APAC/Role=Researcher" from "gin.ggf.nl" can
[104]         execute action "http://authz-interop.org/xacml/action/action-type/access" on the
[105]         Resource "http://authz-interop.org/xacml/resource/resource-type/se" from Target
[106]     </Description>
[107]     <Target>
[108]         <Actions>
[109]             <Action>
[110]                 <ActionMatch
[111] MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[112]                     <AttributeValue
[113]                         DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
[114] interop.org/xacml/action/action-type/access</AttributeValue>
[115]                     <ActionAttributeDesignator
[116]                         AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
[117]                         DataType="http://www.w3.org/2001/XMLSchema#string"/>
[118]                             </ActionMatch>
[119]                                 </Action>
[120]                                     </Actions>
[121] </Target>
[122] <Condition>
[123]     <Apply
[124]         FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-bag">
[125]             <AttributeValue
[126]                 DataType="http://www.w3.org/2001/XMLSchema#string">/gin.ggf.nl/APAC/Role=VO-
[127] Admin</AttributeValue>
[128]             <AttributeValue
[129]                 DataType="http://www.w3.org/2001/XMLSchema#string">/gin.ggf.nl/APAC/Role=Researcher
[130] </AttributeValue>
[131]             <SubjectAttributeDesignator
[132]                 AttributeId="http://authz-interop.org/xacml/subject/voms-primary-fqan"
[133]                 DataType="http://www.w3.org/2001/XMLSchema#string"/>
[134] </Apply>

```

```

[110]     </Condition>
[111] </Rule>
[112] <Obligations>
[113]     <Obligation ObligationId="http://authz-interop.org/xacml/obligation/uidgid"
FulfillOn="Permit">
[114]         <AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-uid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2501</AttributeAssignment>
[115]         <AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-gid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2101</AttributeAssignment>
[116]     </Obligation>
[117] </Obligations>
[118] </Policy>

```

## A.2 Example of Request/Response and Policy with simple negotiation between PEP and PDP about supported Obligations

This example demonstrates simple negotiation procedure between PEP and PDP about supported Obligations. For this purpose the PEP sends a Request message that contains the list of supported Obligations in the Environment element.

a) Request message that contains information about supporting Obligations in lines [163-178]

```

[119] <?xml version="1.0" encoding="UTF-8"?>
[120] <Request
[121]     xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
[122]     xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
[123]     xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os
[124]         access_control-xacml-2.0-context-schema-os.xsd">
[125]     <!-- Example - Request: Supported Obligations negotiation - List of supported
by PEP Obligations are communicated as the Environment Attribute -->
[126]     <Subject>
[127]         <Attribute
[128]             AttributeId="http://authz-interop.org/xacml/subject/subject-x509-id"
[129]             DataType="http://www.w3.org/2001/XMLSchema#string">
[130]                 <AttributeValue>/O=dutchgrid/O=users/O=nikhef/CN=Wim
Huizinga</AttributeValue>
[131]         </Attribute>
[132]         <Attribute
[133]             AttributeId="http://authz-interop.org/xacml/subject/subject-x509-
issuer"
[134]             DataType="http://www.w3.org/2001/XMLSchema#string">
[135]                 <AttributeValue>/C=NL/O=NIKHEF/CN=NIKHEF medium-security certification
auth</AttributeValue>
[136]         </Attribute>
[137]         <Attribute
[138]             AttributeId="http://authz-interop.org/xacml/subject/vo"
[139]             DataType="http://www.w3.org/2001/XMLSchema#string">
[140]                 <AttributeValue>gin.ggf.nl</AttributeValue>
[141]         </Attribute>
[142]         <Attribute
[143]             AttributeId="http://authz-interop.org/xacml/subject/voms-primary-fqan"
[144]             DataType="http://www.w3.org/2001/XMLSchema#string">
[145]                 <AttributeValue>/gin.ggf.nl/APAC/Role=VO-Admin</AttributeValue>

```

```

[146]     </Attribute>
[147] </Subject>
[148] <Resource>
[149]   <Attribute
[150]     AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
[151]     DataType="http://www.w3.org/2001/XMLSchema#anyURI">
[152]     <AttributeValue>http://authz-interop.org/xacml/resource/resource-
type/ce</AttributeValue>
[153]   </Attribute>
[154] </Resource>
[155] <Action>
[156]   <Attribute
[157]     AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
[158]     DataType="http://www.w3.org/2001/XMLSchema#string">
[159]     <AttributeValue>http://authz-interop.org/xacml/action/action-type/execute-
now</AttributeValue>
[160]   </Attribute>
[161] </Action>
[162] <Environment>
[163]   <Attribute
[164]     AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-
supported"
[165]     DataType="http://www.w3.org/2001/XMLSchema#string">
[166]     <AttributeValue>"http://authz-
interop.org/xacml/obligation/uidgid</AttributeValue>
[167]   </Attribute>
[168]   <Attribute
[169]     AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-
supported"
[170]     DataType="http://www.w3.org/2001/XMLSchema#string">
[171]     <AttributeValue>http://authz-interop.org/xacml/obligation/secondary-
gids</AttributeValue>
[172]   </Attribute>
[173]   <Attribute
[174]     AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-
supported"
[175]     DataType="http://www.w3.org/2001/XMLSchema#string">
[176]     <AttributeValue>http://authz-
interop.org/xacml/obligation/username</AttributeValue>
[177]   </Attribute>
[178] </Environment>
[179] </Request>

```

b) Response message with returned obligations in lines [188-193] to map user identity to returned UID and GID under which the user task/request will be executed.

```

[180] <?xml version="1.0" encoding="UTF-8"?>
[181] <Response xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xacml="urn:oasis:names:tc:xacml:2.0:policy:schema:os"
[182] xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os
access_control-xacml-2.0-context-schema-os.xsd">
[183]   <Result ResourceId=" http://authz-interop.org/xacml/resource/resource-type/ce">
[184]     <Decision>Permit</Decision>
[185]     <Status>
[186]       <StatusCode Value="urn:oasis:names:tc:xacml:1.0:status:ok"/>
[187]     </Status>
[188]     <xacml:Obligations>
[189]       <xacml:Obligation ObligationId="http://authz-
interop.org/xacml/obligation/uidgid" FulfillOn="Permit">

```

```

[190]         <xacml:AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-uid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2501</xacml:AttributeAssignment
>
[191]         <xacml:AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-gid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2001</xacml:AttributeAssignment
>
[192]             </xacml:Obligation>
[193]     </xacml:Obligations>
[194] </Result>
[195] </Response>

```

c) Example policy that checks the list of supported Obligations using matching conditions in the Policy Target Environment in lines [226-235]. If the pep-oblig-supported attribute in the request does not contain the username or uidgid obligations, this policy evaluates to “Not applicable”.

```

[196] <?xml version="1.0" encoding="UTF-8"?>
[197] <Policy xmlns="urn:oasis:names:tc:xacml:2.0:policy:schema:os" xmlns:xacml-
context="urn:oasis:names:tc:xacml:2.0:context:schema:os"
xmlns:md="http://www.medico.com/schemas/record"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:policy:schema:os
[198]     access_control-xacml-2.0-policy-schema-os.xsd" PolicyId="http://authz-
interop.org/xacml/example/example852/policy"
RuleCombiningAlgId="urn:oasis:names:tc:xacml:1.0:rule-combining-algorithm:deny-
overrides">
[199]     <Description>
[200]         Example 852 - Policy: Supported obligations negotiation - Sending list
of supported obligations as multiple Environment attributes.
[201]         In a simple case Policy Target must match all supported Obligations
[202]     </Description>
[203]     <PolicyDefaults>
[204]         <XPathVersion>http://www.w3.org/TR/1999/Rec-xpath-
19991116</XPathVersion>
[205]     </PolicyDefaults>
[206]     <Target>
[207]         <Subjects>
[208]             <Subject>
[209]                 <SubjectMatch
MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[210]                     <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#string">
[211]                         gin.ggf.nl</AttributeValue>
[212]                     <SubjectAttributeDesignator
SubjectCategory="urn:oasis:names:tc:xacml:1.0:subject-category:access-subject"
AttributeId="http://authz-interop.org/xacml/subject/vo"
DataType="http://www.w3.org/2001/XMLSchema#string"/>
[213]                     </SubjectMatch>
[214]                 </Subject>
[215]             </Subjects>
[216]             <Resources>
[217]                 <Resource>
[218]                     <ResourceMatch
MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[219]                         <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#URI">http://authz-
interop.org/xacml/resource/resource-type/ce
[220]                         </AttributeValue>

```

```

[ 221]             <ResourceAttributeDesignator
AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-id"
DataType="http://www.w3.org/2001/XMLSchema#URI" />
[ 222]             </ResourceMatch>
[ 223]         </Resource>
[ 224]     </Resources>
[ 225]     <Environments>
[ 226]         <Environment>
[ 227]             <EnvironmentMatch
MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[ 228]                 <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
interop.org/xacml/obligation/uidgid</AttributeValue>
[ 229]                 <EnvironmentAttributeDesignator
AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-supported"
DataType="http://www.w3.org/2001/XMLSchema#string" />
[ 230]                 </EnvironmentMatch>
[ 231]             <EnvironmentMatch
MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[ 232]                 <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
interop.org/xacml/obligation/username</AttributeValue>
[ 233]                 <EnvironmentAttributeDesignator
AttributeId="http://authz-interop.org/xacml/environment/pep-oblig-supported"
DataType="http://www.w3.org/2001/XMLSchema#string" />
[ 234]                 </EnvironmentMatch>
[ 235]             </Environment>
[ 236]     </Environments>
[ 237] </Target>
[ 238] <Rule RuleId="http://authz-
interop.org/xacml/example/example852/policy/rule01" Effect="Permit">
[ 239]     <Description>
[ 240]         User with role "/gin.ggf.nl/APAC/Role=VO-Admin" from "gin.ggf.nl" can
execute action "http://authz-interop.org/xacml/action/action-type/execute-now" on
the Resource "http://authz-interop.org/xacml/resource/resource-type/ce" from Target
[ 241]     </Description>
[ 242]     <Target>
[ 243]         <Actions>
[ 244]             <Action>
[ 245]                 <ActionMatch
MatchId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[ 246]                     <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
interop.org/xacml/action/action-type/execute-now</AttributeValue>
[ 247]                     <ActionAttributeDesignator
AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
DataType="http://www.w3.org/2001/XMLSchema#string" />
[ 248]                     </ActionMatch>
[ 249]                 </Action>
[ 250]             </Actions>
[ 251]         </Target>
[ 252]     <Condition>
[ 253]         <Apply
FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-bag">
[ 254]             <AttributeValue
DataType="http://www.w3.org/2001/XMLSchema#string">/gin.ggf.nl/APAC/Role=VO-
Admin</AttributeValue>
[ 255]             <SubjectAttributeDesignator
AttributeId="http://authz-interop.org/xacml/subject/voms-primary-fqan"
DataType="http://www.w3.org/2001/XMLSchema#string" />
[ 256]             </Apply>
[ 257]         </Condition>
[ 258]     </Rule>
[ 259] </Obligations>

```

```

[260]         <Obligation ObligationId="http://authz-
interop.org/xacml/obligation/UIDGID" FulfillOn="Permit">
[261]             <AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-uid"
[262]             <AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-gid"
[263]             </Obligation>
[264]         </Obligations>
[265] </Policy>

```

### A.3 Example of Request/Response and Policy for Pilot Job submitting to Worker Node

a) Request message that contains information about the Pilot Job submitter in the Environment element in lines [291-302]

```

[266] <?xml version="1.0" encoding="UTF-8"?>
[267] <Request xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os
[268]     access_control-xacml-2.0-context-schema-os.xsd">
[269]     <!-- Example - Request: Requesting decision from WN when submitting user job
from the Pilot Job - (full) information about the PJ submitter Subject is included
in the Environment attribute -->
[270]     <Subject>
[271]         <Attribute AttributeId="http://authz-interop.org/xacml/subject/subject-
x509-id" DataType="http://www.w3.org/2001/XMLSchema#string">
[272]             <AttributeValue>/O=dutchgrid/O=users/O=nikhef/CN=Wim
Huizinga</AttributeValue>
[273]         </Attribute>
[274]         <Attribute AttributeId="http://authz-interop.org/xacml/subject/vo"
[275]             <AttributeValue>gin.ggf.nl</AttributeValue>
[276]         </Attribute>
[277]         <Attribute AttributeId="http://authz-interop.org/xacml/subject/voms-
primary-fqan" DataType="http://www.w3.org/2001/XMLSchema#string">
[278]             <AttributeValue>/gin.ggf.nl/APAC/Role=Researcher</AttributeValue>
[279]         </Attribute>
[280]     </Subject>
[281]     <Resource>
[282]         <Attribute AttributeId="urn:oasis:names:tc:xacml:1.0:resource:resource-
id" DataType="http://www.w3.org/2001/XMLSchema#anyURI">
[283]             <AttributeValue>http://authz-interop.org/xacml/resource/resource-
type/wn</AttributeValue>
[284]         </Attribute>
[285]     </Resource>
[286]     <Action>
[287]         <Attribute AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
[288]             <AttributeValue>http://authz-interop.org/xacml/action/action-
type/execute-now</AttributeValue>
[289]         </Attribute>
[290]     </Action>
[291]     <Environment>
[292]         <!-- Here Subject attributes of the Pilot Job submitter are included -->
[293]         <Attribute AttributeId="http://authz-interop.org/xacml/environment/pilot-
job/subject-id" DataType="http://www.w3.org/2001/XMLSchema#string">
[294]             <AttributeValue>/O=dutchgrid/O=users/O=nikhef/CN=Joop van der
Hoek</AttributeValue>

```

```

[295]         </Attribute>
[296]         <Attribute AttributeId="http://authz-interop.org/xacml/environment/pilot-
job/vo" DataType="http://www.w3.org/2001/XMLSchema#string">
[297]             <AttributeValue>gin.ggf.nl</AttributeValue>
[298]         </Attribute>
[299]         <Attribute AttributeId="http://authz-interop.org/xacml/environment/voms-
primary-fqan" DataType="http://www.w3.org/2001/XMLSchema#string">
[300]             <AttributeValue>/gin.ggf.nl/APAC/Role=VO-services-
manager</AttributeValue>
[301]         </Attribute>
[302]     </Environment>
[303] </Request>

```

b) Response message with returned obligations in lines [318-323] to map user identity to returned UID and GID under which the user task/request will be executed.

```

[304] <?xml version="1.0" encoding="UTF-8"?>
[305] <Response xmlns="urn:oasis:names:tc:xacml:2.0:context:schema:os"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xacml="urn:oasis:names:tc:xacml:2.0:policy:schema:os"
[306] xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:context:schema:os
access_control-xacml-2.0-context-schema-os.xsd">
[307]     <Result ResourceId="http://authz-interop.org/xacml/resource/resource-type/ce">
[308]         <Decision>Permit</Decision>
[309]         <Status>
[310]             <StatusCode Value="urn:oasis:names:tc:xacml:1.0:status:ok"/>
[311]         </Status>
[312]         <xacml:Obligations>
[313]             <xacml:Obligation ObligationId="http://authz-
interop.org/xacml/obligation/uidgid" FulfillOn="Permit">
[314]                 <xacml:AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-uid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2501</xacml:AttributeAssignment
>
[315]                 <xacml:AttributeAssignment AttributeId="http://authz-
interop.org/xacml/attribute/posix-gid"
DataType="http://www.w3.org/2001/XMLSchema#integer">2001</xacml:AttributeAssignment
>
[316]             </xacml:Obligation>
[317]         </xacml:Obligations>
[318]     </Result>
[319] </Response>

```

c) Example policy allows matching between pilot request/owner VO and pilot job submitter VO.

- Policy contains two rules: rule001 in lines [364-374] that checks user attribute, and rule002 in lines [375-391] that compares pilot request/owner VO and pilot job submitter VO
- AttributeSelect in the Apply element uses XPath expression in lines [386] to obtain submitters VO information from the Environment element in the Request

```

[320] <?xml version="1.0" encoding="UTF-8"?>
[321] <Policy
[322]     xmlns="urn:oasis:names:tc:xacml:2.0:policy:schema:os"
[323]     xmlns:xacml-context="urn:oasis:names:tc:xacml:2.0:context:schema:os"
[324]     xmlns:md="http://www.medico.com/schemas/record"
[325]     xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"

```

```

[326]     xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:policy:schema:os
[327]         access_control-xacml-2.0-policy-schema-os.xsd"
[328]     PolicyId="http://authz-interop.org/xacml/example/policy/example832/policy"
[329]     RuleCombiningAlgId="urn:oasis:names:tc:xacml:1.0:rule-combining-
algorithm:deny-overrides">
[330]     <Description>
[331]         Example - Policy Pilot job submission at WN: When submitting the User/real
job the User VO must match the Pilot Job submitter VO provided in the Environment
element.
[332]     </Description>
[333]     <PolicyDefaults>
[334]         <XPathVersion>http://www.w3.org/TR/1999/Rec-xpath-19991116</XPathVersion>
[335]     </PolicyDefaults>
[336]     <Target>
[337]         <Subjects>
[338]             <Subject>
[339]                 <SubjectMatch MatchId="urn:oasis:names:tc:xacml:1.0:function:string-
equal">
[340]                     <AttributeValue
[341]                         DataType="http://www.w3.org/2001/XMLSchema#string">gin.ggf.nl</AttributeValue>
[342]                     <SubjectAttributeDesignator
[343]                         SubjectCategory="urn:oasis:names:tc:xacml:1.0:subject-category:access-subject"
[344]                         AttributeId="http://authz-interop.org/xacml/subject/vo"
[345]                         DataType="http://www.w3.org/2001/XMLSchema#string"/>
[346]                     </SubjectMatch>
[347]                 </Subject>
[348]             </Subjects>
[349]             <Resources>
[350]                 <Resource>
[351]                     <ResourceMatch MatchId="urn:oasis:names:tc:xacml:1.0:function:string-
equal">
[352]                         <AttributeValue
[353]                             DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
interop.org/xacml/resource/resource-type/wn
[354]                         </AttributeValue>
[355]                     </ResourceMatch>
[356]                 </Resource>
[357]             </Resources>
[358]             <Actions>
[359]                 <Action>
[360]                     <ActionMatch MatchId="urn:oasis:names:tc:xacml:1.0:function:string-
equal">
[361]                         <AttributeValue
[362]                             DataType="http://www.w3.org/2001/XMLSchema#string">http://authz-
interop.org/xacml/action/action-type/execute-now</AttributeValue>
[363]                         <ActionAttributeDesignator
[364]                             AttributeId="urn:oasis:names:tc:xacml:1.0:action:action-id"
[365]                             DataType="http://www.w3.org/2001/XMLSchema#string"/>
[366]                         </ActionMatch>
[367]                     </Action>
[368]                 </Actions>
[369]             </Target>
[370]         <Rule RuleId="http://authz-
interop.org/xacml/example/policy/example832/rule001" Effect="Permit">
[371]             <Description>
[372]                 Rule001: User with role "/gin.ggf.nl/APAC/Role=Researcher" from
"gin.ggf.nl" can execute action "http://authz-interop.org/xacml/action/action-
type/execute-now" on the Resource under condition of Rule002 [373]
[373]             </Description>
[374]         </Rule>
[375]     </Target/>

```

```

[368]     <Condition>
[369]         <Apply FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[370]             <AttributeValue
                DataType="http://www.w3.org/2001/XMLSchema#string">/gin.ggf.nl/APAC/Role=Researcher
            </AttributeValue>
[371]             <SubjectAttributeDesignator AttributeId="http://authz-
                interop.org/xacml/subject/voms-primary-fqan"
                DataType="http://www.w3.org/2001/XMLSchema#string" />
[372]             </Apply>
[373]         </Condition>
[374]     </Rule>
[375]     <Rule RuleId="http://authz-
                interop.org/xacml/example/policy/example832/rule002" Effect="Permit">
[376]         <Description>
[377]             Rule002: Additional conditionthat the User "subject/vo" matches Pilot
                Job submitter "environment/vo".
[378]         </Description>
[379]         <Target/>
[380]         <Condition>
[381]             <Apply FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-equal">
[382]                 <Apply FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-bag">
[383]                     <SubjectAttributeDesignator AttributeId="http://authz-
                        interop.org/xacml/subject/vo" DataType="http://www.w3.org/2001/XMLSchema#string" />
                    [391] </Apply>
[384]                     <Apply FunctionId="urn:oasis:names:tc:xacml:1.0:function:string-bag">
[385]                         <AttributeSelector
                            DataType="http://www.w3.org/2001/XMLSchema#string"
[386]                             RequestContextPath="./xacml-context:Environment/xacml-
                                context:Attribute(@AttributeId, 'http://authz-interop.org/xacml/environment/pilot-
                                    job/vo')/xacml-context:AttributeValue/text()"
[387]                             />
[388]                         </Apply>
[389]                     </Apply>
[390]                 </Condition>
[391]             </Rule>
[392]         <Obligations>
[393]             <Obligation ObligationId="http://authz-
                interop.org/xacml/obligation/uidgid" FulfillOn="Permit">
[394]                 <AttributeAssignment AttributeId="http://authz-
                    interop.org/xacml/attribute/posix-uid"
                    DataType="http://www.w3.org/2001/XMLSchema#integer">2501</AttributeAssignment>
[395]                 <AttributeAssignment AttributeId="http://authz-
                    interop.org/xacml/attribute/posix-gid"
                    DataType="http://www.w3.org/2001/XMLSchema#integer">2101</AttributeAssignment>
[396]             </Obligation>
[397]         </Obligations>
[398]     </Policy>

```

## **Appendix B: List of Attribute and Obligation IDs introduced by this profile**

### **Subject Context**

*http://authz-interop.org/xacml/subject/subject-x509-id*

*http://authz-interop.org/xacml/subject/subject-condor-canonical-name-id*

*http://authz-interop.org/xacml/subject/subject-x509-issuer*

*http://authz-interop.org/xacml/subject/vo*

*http://authz-interop.org/xacml/subject/voms-signing-subject*

<http://authz-interop.org/xacml/subject/voms-signing-issuer>  
<http://authz-interop.org/xacml/subject/voms-fqan>  
<http://authz-interop.org/xacml/subject/voms-primary-fqan>

#### **Optional Attributes:**

<http://authz-interop.org/xacml/subject/certificate-serial-number>  
<http://authz-interop.org/xacml/subject/ca-serial-number>  
<http://authz-interop.org/xacml/subject/voms-dns-port>  
<http://authz-interop.org/xacml/subject/ca-policy-oid>  
<http://authz-interop.org/xacml/subject/cert-chain>

#### **Action Context**

Enumeration of possible values for *urn:oasis:names:tc:xacml:1.0:action:action-id* :

<http://authz-interop.org/xacml/action/action-type/queue>  
<http://authz-interop.org/xacml/action/action-type/execute-now>  
<http://authz-interop.org/xacml/action/action-type/access>  
<http://authz-interop.org/xacml/action/rsl-string>

#### **Resource Context**

Enumeration of possible values for *urn:oasis:names:tc:xacml:1.0:resource:resource-id* :

<http://authz-interop.org/xacml/resource/resource-type/ce>  
<http://authz-interop.org/xacml/resource/resource-type/se>  
<http://authz-interop.org/xacml/resource/resource-type/wn>  
<http://authz-interop.org/xacml/resource/dns-host-name>  
<http://authz-interop.org/xacml/resource/resource-x509-id>  
<http://authz-interop.org/xacml/resource/resource-x509-issuer>

#### **Environment Context**

<http://authz-interop.org/xacml/environment/pilot-job/pep-oblig-supported>  
<http://authz-interop.org/xacml/environment/pilot-job/subject-x509-id>  
<http://authz-interop.org/xacml/environment/pilot-job/subject-condor-canonical-name-id>  
<http://authz-interop.org/xacml/environment/pilot-job/subject-x509-issuer>  
<http://authz-interop.org/xacml/environment/pilot-job/vo>  
<http://authz-interop.org/xacml/environment/pilot-job/voms-signing-subject>  
<http://authz-interop.org/xacml/environment/pilot-job/voms-signing-issuer>  
<http://authz-interop.org/xacml/environment/pilot-job/voms-fqan>  
<http://authz-interop.org/xacml/environment/pilot-job/voms-primary-fqan>

#### **Obligation Context and Attributes**

<http://authz-interop.org/xacml/obligation/uidgid>  
<http://authz-interop.org/xacml/attribute/posix-uid>  
<http://authz-interop.org/xacml/attribute/posix-uid>

<http://authz-interop.org/xacml/obligation/secondary-gids>  
<http://authz-interop.org/xacml/attribute/posix-gid>

*http://authz-interop.org/xacml/obligation/username*  
*http://authz-interop.org/xacml/attribute/username*

*http://authz-interop.org/xacml/obligation/afs-token*  
*http://authz-interop.org/xacml/attribute/afs-token*

*http://authz-interop.org/xacml/obligation/root-and-home-paths*  
*http://authz-interop.org/xacml/attribute/rootpath*  
*http://authz-interop.org/xacml/attribute/homepath*

*http://authz-interop.org/xacml/obligation/storage-access-priority*  
*http://authz-interop.org/xacml/attribute/storage-priority*

*http://authz-interop.org/xacml/obligation/access-permissions*  
*http://authz-interop.org/xacml/attribute/access-permissions*

## **References**

[XACML] “eXtensible Access Control Markup Language (XACML) Version 2.0”

[http://docs.oasis-open.org/xacml/2.0/access\\_control-xacml-2.0-core-spec-os.pdf](http://docs.oasis-open.org/xacml/2.0/access_control-xacml-2.0-core-spec-os.pdf)

[XMLSchema] “XML Schema Part 2: Datatype 2<sup>nd</sup> Edition”:

<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>

[RSL] “GT 2.4: The Globus Resource Specification Language RSL v1.0”

[http://www.globus.org/toolkit/docs/2.4/gram/rsl\\_spec1.html](http://www.globus.org/toolkit/docs/2.4/gram/rsl_spec1.html)