

Tutorial on Computational Social Choice

Table of Contents

Introduction	3
Preference Aggregation	10
Manipulation of Voting Procedures	18
Voting in Combinatorial Domains	37
Judgment Aggregation	46
Fair Division	55
Conclusion	73

[<http://www.illc.uva.nl/~ulle/teaching/ecai-2010/>]

Ulle Endriss
1

Computational Social Choice
ECAI-2010
2

Computational Social Choice
ECAI-2010
3

Computational Social Choice
ECAI-2010
4

Social Choice Theory

SCT studies collective decision making: how should we aggregate the preferences of the members of a group to obtain a "social preference"?

$$\begin{array}{c} \Delta \succ_1 \circ \succ_1 \square \\ \square \succ_2 \Delta \succ_2 \circ \\ \circ \succ_3 \square \succ_3 \Delta \\ \hline ? \end{array}$$

Ulle Endriss
3

Computational Social Choice
ECAI-2010
4

Computational Social Choice
ECAI-2010
5

Computational Social Choice
ECAI-2010
6

The COMSOC Research Community

- International Workshop on Computational Social Choice:
 - 1st edition: COMSOC-2006 in Amsterdam, December 2006
 - 48 paper submissions and 80 participants (14 countries)
 - 2nd edition: COMSOC-2008 in Liverpool, September 2008
 - 55 paper submissions and ~80 participants (~20 countries)
 - 3rd edition: COMSOC-2010 in Düsseldorf, September 2010
 - 58 paper submissions
- Special issues in international journals.
 - *Mathematical Logic Quarterly*, vol. 55, no. 4, 2009
 - *Journal of Autonomous Agents and Multiagent Systems* (2011)
 - *Mathematical Social Sciences* (in preparation)
- Journals and conferences in AI, MAS, TCS, Logic, Econ, ...
 - COMSOC website: <http://www.illc.uva.nl/COMSOC/>

Ulle Endriss
5

Computational Social Choice
ECAI-2010
6

Computational Social Choice
ECAI-2010
7

Social Choice and AI (1)

Social Choice theory has natural applications in AI:

- **Search Engines**: to determine the most important sites based on links ("votes") + to aggregate the output of several search engines
- **Recommender Systems**: to recommend a product to a user based on earlier ratings by other users
- **Multigagent Systems**: to aggregate the beliefs + to coordinate the actions of groups of autonomous software agents
- **AI Competitions**: to determine who has developed the best trading agent / SAT solver / RoboCup team
- But not all of the classical assumptions will fit these new applications.
- So AI needs to develop *new models* and *ask new questions*.

Computational Social Choice
ECAI-2010
8

Social Choice and AI (2)

Vice versa, techniques from AI, and computational techniques in general, are useful for advancing the state of the art in social choice:

- **Algorithms and Complexity**: to develop algorithms for (complex) voting procedures + to understand the hardness of "using" them
 - **Knowledge Representation**: to compactly represent the preferences of individual agents over large spaces of alternatives
 - **Logic and Automated Reasoning**: to formally model problems in social choice + to automatically verify (or discover) theorems
- Indeed, you will find many papers on social choice at AI conferences (e.g., IJCAI, ECAI, AAAI, AAMAS) and many AI researchers participate in events dedicated to social choice (e.g., COMSOC).

This Tutorial

The aim of this tutorial is to give a tentative overview of the COMSOC research area, highlighting contributions of and opportunities for AI.

We will concentrate on these topics:

- Preference Aggregation
- Manipulation of Voting Procedures
- Voting in Combinatorial Domains
- Judgment Aggregation
- Fair Division

Ulf Endriss

9

Computational Social Choice

ECAI-2010

Preference Aggregation: Formal Framework

Problem: How can we amalgamate the preferences of a group of individuals into a collective preference order?

Basic terminology and notation:

- finite set of *individuals* $N = \{1, \dots, n\}$
- (usually finite) set of *alternatives* $\mathcal{X} = \{x_1, x_2, x_3, \dots\}$
- Denote the set of *linear orders* on \mathcal{X} by $\mathcal{L}(\mathcal{X})$.

Preferences are assumed to be elements of $\mathcal{L}(\mathcal{X})$.

A *social welfare function* is a function $F : \mathcal{L}(\mathcal{X})^n \rightarrow \mathcal{L}(\mathcal{X})$, mapping profiles of individual preference orders to a societal preference order.

Ulf Endriss

11

Computational Social Choice

ECAI-2010

Ulf Endriss

10

Computational Social Choice

ECAI-2010

Axioms: Some Natural Desiderata

It seems reasonable to postulate that any aggregator F should satisfy the following list of axioms:

- **(WP)** F should satisfy the *weak Pareto condition*: if every individual prefers x over y , then so should society.
- **(IIA)** F should satisfy *independence of irrelevant alternatives*: the relative social ranking of x and y should depend only on the relative individual rankings of x and y .
- **(ND)** F should be *nondictatorial*: no single individual should be able to impose the social preference ordering.

Ulf Endriss

12

Computational Social Choice

ECAI-2010

Ulf Endriss

13

Computational Social Choice

ECAI-2010

Arrow's Theorem

This is widely regarded as *the* seminal result in Social Choice Theory.

Kenneth J. Arrow received the Nobel Prize in Economics in 1972.

Theorem 1 (Arrow, 1951) There exists **no** social welfare function for ≥ 3 alternatives that satisfies all of (WP), (IIA) and (ND).

Remarks.

- Note that this is a *surprising* result!
- Note that the theorem does *not* hold for **two** alternatives.

K.J. Arrow. *Social Choice and Individual Values*. 2nd edition. Cowles Foundation, Yale University Press, 1963.

J. Geanakoplos. Three Brief Proofs of Arrow's Impossibility Theorem. *Economic Theory*, 26(1):211–215, 2005.

Computational Social Choice

ECAI-2010

Ulf Endriss

14

Computational Social Choice

ECAI-2010

Logic and Automated Reasoning

Logic has long been used to *formally specify* computer systems, facilitating formal or even *automatic verification* of various properties. Can we apply this methodology also to *social choice* mechanisms?

- What logic fits best?
- Which automated reasoning methods are useful?

Computational Social Choice

ECAI-2010

Computer-aided Proof of Arrow's Theorem

Tang and Lin (2009) prove two inductive lemmas:

- If there exists an Arrowian aggregator for n individuals and $m+1$ alternatives, then there exists one for n and m (if $n \geq 2, m \geq 3$).
- If there exists an Arrowian aggregator for $n+1$ individuals and m alternatives, then there exists one for n and m (if $n \geq 2, m \geq 3$). Tang and Lin then show that the “*base case*” of Arrow’s Theorem with 2 individuals and 3 alternatives can be modelled in *propositional logic*. A SAT solver can *verify* Arrow($2, 3$) to be correct in < 1 second — that’s $|3\rangle^{3 \times 3} \approx 10^{28}$ aggregators to check.

Discussion: Opens up opportunities for quick sanity checks of hypotheses regarding new impossibility theorems.

P. Tang and F. Lin. Computer-aided Proofs of Arrow’s and other Impossibility Theorems. *Artificial Intelligence*, 173(1):1041–1053, 2009.

Computational Social Choice

ECAI-2010

Related Work

- Agotnes et al. (2010) propose a modal logic to model preferences and their aggregation that can express Arrow’s Theorem.
- Arrow’s Theorem holds iff the set T_{Arrow} of FOL formulas (defined in the paper) has no finite models (Grandi and E., 2009).
- Nipkow (2009) formalises and verifies a known proof of Arrow’s Theorem in the HOL proof assistant ISABELLE.

Computational Social Choice

ECAI-2010

Ulf Endriss

15

Literature

Arrow's Theorem is the seminal example for the use of the **axiomatic method** in social choice theory. To learn more, refer to the textbooks by Gaertner (2009) and Taylor (2005).

A comprehensive approach for formalisation (with **symbolic languages**) of concepts from social choice theory and applications of automated reasoning technology is yet to be developed. For a host of ideas along (roughly) those lines, read Parikh (2002) on "social software".

W. Gaertner. *A Primer in Social Choice Theory*. Revised edition, LSE Perspectives in Economic Analysis. Oxford University Press, 2009.

A.D. Taylor. *Social Choice and the Mathematics of Manipulation*. Cambridge University Press, 2005.

R. Parikh. Social Software. *Synthese*, 132(3):187–211, 2002.

[Ulf Endress](#) [ECAI-2010](#)

[Computational Social Choice](#) [ECAI-2010](#)

Example

Suppose the **plurality rule** is used to decide an election: the candidate receiving the highest number of votes wins.

Assume the preferences of the people in, say, Florida are as follows:

49%:	Bush > Gore > Nader
20%:	Gore > Nader > Bush
20%:	Gore > Bush > Nader
11%:	Nader > Gore > Bush

So even if nobody is cheating, Bush will win this election. But:

- In a **pairwise contest**, Gore would have defeated anyone.
- It would have been in the interest of the Nader supporters to **manipulate**, i.e., to misrepresent their preferences.

Is there a better voting procedure that avoids these problems?

[Ulf Endress](#) [ECAI-2010](#)

[Computational Social Choice](#) [ECAI-2010](#)

Voting: Formal Framework

Basic terminology and notation:

- finite set of **voters** $\mathcal{N} = \{1, \dots, n\}$, the **electorate**
- (usually finite) set of **alternatives/candidates** $\mathcal{X} = \{x_1, x_2, x_3, \dots\}$
- Denote the set of **linear orders** on \mathcal{X} by $\mathcal{L}(\mathcal{X})$. **Preferences** are assumed to be elements of $\mathcal{L}(\mathcal{X})$. **Ballots** are elements of $\mathcal{L}(\mathcal{X})$.

A **voting procedure** is a function $F: \mathcal{L}(\mathcal{X})^n \rightarrow 2^{\mathcal{X}} \setminus \{\emptyset\}$, mapping profiles of ballots to nonempty sets of alternatives (**winners**).

F is called **resolute** if $F(b)$ is a singleton for any profile $b \in \mathcal{L}(\mathcal{X})^n$.

Remark: AV does not fit in this framework; everything else does.

[Ulf Endress](#) [ECAI-2010](#)

[Computational Social Choice](#) [ECAI-2010](#)

Strategy-Proofness

Let \succ_i be the true preference of voter i and let b_i be the ballot of i .

A resolute voting procedure F is **strategy-proof** if there exist no profile $b = (b_1, \dots, b_n)$ and no voter i s.t. $F(b_1, \dots, \succ_i, \dots, b_n)$, with \succ_i lifted from alternatives to singletons in the natural manner. That is,

- A voting procedure is strategy-proof if it never gives a voter an incentive to misrepresent her true preferences.

Remarks:

- We have seen that the **plurality rule** is not strategy-proof.
- Any **dictatorial** rule (where the unique winner is always the top choice of the dictator) clearly is strategy-proof.

[Ulf Endress](#) [ECAI-2010](#)

[Computational Social Choice](#) [ECAI-2010](#)

The Gibbard-Satterthwaite Theorem

A resolute voting procedure F is **subjective** if for any alternative x there exists a ballot profile b such that $F(b) = \{x\}$.

Theorem 2 (Gibbard-Satterthwaite) Any resolute voting procedure for ≥ 3 alternatives that is subjective and strategy-proof is dictatorial.

Remarks:

- Again, surprising: Again, not applicable for two alternatives.
- Random procedures don't count (but might be "strategy-proof").

What to do?

The Gibbard-Satterthwaite tells us (essentially) that there are no reasonable voting procedures that are strategy-proof. That's very bad! We will consider three possible avenues to circumvent this problem:

- Restricting the domain (the classical approach)
- Changing the formal framework a little
- Making manipulation computationally hard

[Ulf Endress](#) [ECAI-2010](#)

[Computational Social Choice](#) [ECAI-2010](#)

Intractability of Manipulating STV

Recall STV: eliminate plurality losers until an alternative gets $> 50\%$
Theorem 4 (Bartholdi and Orlin, 1991) *Manipulation of STV is NP-complete.*

Discussion: NP is a worst-case notion. What about average complexity?

J.J. Bartholdi III and J.B. Orlin. Single Transferable Vote Resists Strategic Voting. *Social Choice and Welfare*, 8(4):341–354, 1991.

P. Faliszewski and A.D. Procaccia. AI's War on Manipulation: Are We Winning? *AI Magazine*. In press (2010).

Ulf Endriss

33

Computational Social Choice

ECAI-2010

Even More on Complexity of Voting

- What is the *communication complexity* of different voting rules, i.e., how much information needs to be exchanged to determine the winner of an election? See Conitzer and Sandholm (2005).
- After having counted part of the vote, can we *compile* this information into a more compact form than just storing all the ballots? And how complex is it to reason about this information? See Chevaleyre et al. (2009).

V. Conitzer and T. Sandholm. Communication Complexity of Common Voting Rules. Proc. ACM Conference on Electronic Commerce 2005.

V. Chevaleyre, J. Lang, N. Maudet, and G. Raviñy-Abadie. Compiling the Votes of a Subelectorate. Proc. IJCAI-2009.

35

Ulf Endriss

Computational Social Choice

ECAI-2010

Literature

The manipulation problem is discussed at great length in the textbook by Taylor (2005), and Gaertner (2001) provides an in-depth discussion of domain restrictions.

Faliszewski and Procaccia (2010) review the literature on exploiting computational complexity as a barrier against manipulation in voting.

A.D. Taylor. *Social Choice and the Mathematics of Manipulation*. Cambridge University Press, 2005.

W. Gaertner. *Domain Conditions in Social Choice Theory*. Cambridge University Press, 2001.

P. Faliszewski and A.D. Procaccia. AI's War on Manipulation: Are We Winning? *AI Magazine*. In press (2010).

Ulf Endriss

Computational Social Choice

ECAI-2010

Voting in Combinatorial Domains

Besides the complexity-theoretic properties of voting procedures, another computational concern in voting is raised by the fact that the alternatives to vote for often have a *combinatorial structure*:

- Electing a committee of k members from amongst n candidates.
- During a referendum (in Switzerland, California, places like that), voters may be asked to vote on several propositions.

We will see an example and look into several possible approaches ...

Based on J. Lang's "5 solutions". Read it in Chevaleyre et al. (2008).
 V. Chevaleyre, U. Endriss, J. Lang, and N. Maudet. Preference Handling in Combinatorial Domains: From AI to Social Choice. *AI Magazine*, 29(4):37–46, 2008.

Ulf Endriss

Computational Social Choice

ECAI-2010

Example

Suppose 13 voters are asked to each vote yes or no on three issues, and we use the plurality rule for each issue independently to select a winning combination:

- 3 voters each vote for YNN, NYN, NNY.
- 1 voter each votes for YYY, YYN, YNY, NYY.
- No voter votes for NNN.

But then NNN wins: 7 out of 13 vote no on each issue.

This is an instance of the *paradox of multiple elections*: the winning combination receives the fewest number of votes.

S.J. Brams, D.M. Kilgour, and W.S. Zwicker. The Paradox of Multiple Elections. *Social Choice and Welfare*, 15(2):211–236, 1998.

Ulf Endriss

Computational Social Choice

ECAI-2010

More on Complexity of Voting

Other questions that have been investigated include:

- What is the complexity of other forms of election manipulation, such as *bribery*? See Faliszewski et al. (2009) for a survey.

- After some of the ballots have been counted, certain candidates may be *possible winners* or even *necessary winners*. How hard is it to check this? See e.g. Konczak and Lang (2005).

P. Faliszewski, E. Hemaspaandra, L.A. Hemaspaandra, and J. Rothe. *A Richer Understanding of the Complexity of Election Systems*. In *Fundamental Problems in Computing*. Springer-Verlag, 2009.

K. Konczak and J. Lang. *Voting Procedures with Incomplete Preferences*. Proc. Advances in Preference Handling 2005.

Ulf Endriss

ECAI-2010

Basic Solution Attempts

- Solution 1: just vote for combinations directly
 - only feasible for very small problem instances
 - Example: 3-seat committee, 10 candidates $\sim \binom{10}{3} = 120$
- Solution 2: vote for top k combinations only (e.g., $k = 1$)
 - does address communication problem of Solution 1
 - possibly nobody gets more than one vote (tie-breaking decides)
- Solution 3: make a small preselection of combinations to vote on
 - does solve the computational problems
 - but who should select? (strategic control)

40

Combinatorial Vote

Idea: Ask voters to report their ballots by means of expressions in a **compact preference representation language** and apply your favourite voting procedure to the succinctly encoded ballots received.

Lang (2004) calls this approach **combinatorial vote**.

Discussion: This seems the most promising approach so far, although not too much is known to date what would be good choices for preference representation languages or voting procedures, or what algorithms to use to compute the winners. Also, complexity can be expected to be very high.

J. Lang. Logical Preference Representation and Combinatorial Vote. *Annals of Mathematics and Artificial Intelligence*, 42(1–3):37–71, 2004.

Ulf Endress

Computational Social Choice

ECAI-2010

Preference Representation Languages

Several languages have been proposed for the compact representation of preference orders. See Lang (2004) for an overview. Examples:

- **Weighted goals**: use propositional logic to express goals; assign weights to express importance; aggregate (e.g., lexicographically)
- **CP-nets**: use a directed graph to express dependence between issues; use conditional preference tables to specify preferences on issue assuming those it depends on are fixed

J. Lang. Logical Preference Representation and Combinatorial Vote. *Annals of Mathematics and Artificial Intelligence*, 42(1–3):37–71, 2004.

Ulf Endress

Computational Social Choice

ECAI-2010

Other Approaches

Vote on each issue separately **but** —

- identify **conditions** under which this does not lead to undesirable outcomes ("separable preferences")
- find a **novel way of aggregating** the ballots to select a winner
 - Example: elect the combination minimising the maximal Hamming distance to any of the ballots (Brams et al., 2007)
- vote **sequentially** rather than simultaneously
 - Example: Lang and Xia (2009) use CP-nets to represent ballots and use the underlying graph as an agenda

S.J. Brams, D.M. Kilgour, and M.R. Sanver. A Minimax Procedure for Electing Committees. *Public Choice*, 132:401–420, 2007.
 J. Lang and L. Xia. Sequential Composition of Voting Rules in Multi-Issue Domains. *Mathematical Social Sciences*, 57(3):304–324, 2009.

Ulf Endress

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

Literature

Chevaleyre et al. (2008) give an introduction to social choice in combinatorial domains.

An important reference is the paper by Lang (2004), which also includes a lot of information regarding the compact representation of (ordinal) preferences.

Judgment Aggregation

V. Chevaleyre, U. Endress, J. Lang, and N. Maudet. Preference Handling in Combinatorial Domains: From AI to Social Choice. *AI Magazine*, 29(4):37–46, 2008.
 J. Lang. Logical Preference Representation and Combinatorial Vote. *Annals of Mathematics and Artificial Intelligence*, 42(1–3):37–71, 2004.

Ulf Endress

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

The Doctrinal Paradox

Story: three judges have to decide whether the defendant is guilty . . .

	p	$p \rightarrow q$	q
Judge 1:	Yes	Yes	Yes
Judge 2:	No	Yes	No
Judge 3:	Yes	No	No
Majority:	Yes	Yes	No

Paradox: each **individual** judgment set is **consistent**, but the **collective** judgment arrived at using the **majority rule** is not

L.A. Kornhauser and L.G. Saager. The One and the Many: Adjudication in Collegial Courts. *California Law Review*, 81(1):1–59, 1993.

Ulf Endress

Computational Social Choice

ECAI-2010

Example

Use the language defined by the *leximin ordering over prioritised goals* with the **Borda rule** (goals are labelled by their rank):

- Voter 1. $\{A|0, B|1\}$ induces order $AB \succ_1 A\bar{B} \succ_1 \bar{A}\bar{B}$
- Voter 2. $\{A \vee \neg B|0\}$ induces order $A\bar{B} \sim_2 AB \sim_2 \bar{A}\bar{B} \succ_2 \bar{A}\bar{B}$
- Voter 3. $\{\neg A|0, B|0\}$ induces order $\bar{A}B \succ_3 AB \sim_3 A\bar{B} \succ_3 A\bar{B}$

As the induced orders need not be strict linear orders, we use a **generalisation of the Borda rule**: a candidate gets as many points as she dominates other candidates. So we get these Borda counts:

$$\begin{array}{ll} AB : 3 + 1 + 1 = 5 & AB : 1 + 0 + 3 = 4 \\ A\bar{B} : 2 + 1 + 0 = 3 & \bar{A}\bar{B} : 0 + 1 + 1 = 2 \end{array}$$

So combination AB wins.

Combinatorial vote **proper** would be to compute the winner *directly* from the goal bases, without the detour via the induced orders.

Ulf Endress

Computational Social Choice

ECAI-2010

Axioms

Use **axioms** to express desiderata for F . Examples:

Anonymity (A): For any profile \mathbf{J} and any permutation $\sigma : \mathcal{N} \rightarrow \mathcal{N}$ we have $F(J_1, \dots, J_n) = F(J_{\sigma(1)}, \dots, J_{\sigma(n)})$.

Neutrality (N): For any φ, ψ in the agenda Φ and profile $\mathbf{J} \in \mathcal{J}(\Phi)$, if for all i we have $\varphi \in J_i \Leftrightarrow \psi \in J_i$, then $\varphi \in F(\mathbf{J}) \Leftrightarrow \psi \in F(\mathbf{J})$.

Independence (I): For any φ in the agenda Φ and profiles \mathbf{J} and \mathbf{J}' in $\mathcal{J}(\Phi)$, if $\varphi \in J_i \Leftrightarrow \varphi \in J'_i$ for all i , then $\varphi \in F(\mathbf{J}) \Leftrightarrow \varphi \in F(\mathbf{J}')$.

Systematicity (S) = (N) + (I)

C. List and C. Puppe, Judgment Aggregation: A Survey. *Handbook of Rational and Social Choice*. Oxford University Press, 2009.

Ulf Endress
59

Computational Social Choice
ECAI-2010

Research in Judgment Aggregation

Some of the questions that have been investigated:

- What impossibilities are there? How can we circumvent them?
 - Relax some of the axioms? Which? Why?
 - Impose domain restrictions?
- What properties characterise agendas for which a given combination of axioms permits a consistent procedure?
- What happens if we change the underlying logic?
- What are acceptable procedures in practice? (that guarantee consistent outcomes but may violate other axioms)
- What are the precise connections to preference aggregation?

C. List and C. Puppe, Judgment Aggregation: A Survey. *Handbook of Rational and Social Choice*. Oxford University Press, 2009.

Ulf Endress
51

Computational Social Choice
ECAI-2010

JA and Argumentation in AI

As an example for uses of JA in AI, Caminada and Pigozzi (2009) apply JA methodology in work on abstract argumentation:

- A directed graph describes the attack-relation between arguments.
- Rules for consistently labelling arguments as accepted, rejected or undecided provide a semantics.

U. Endress, U. Grandi, and D. Porello, Complexity of Judgment Aggregation: Safety of the Agenda. Proc. AAMAS-2010.

U. Endress, U. Grandi, and D. Porello, Complexity of Winner Determination and Strategic Manipulation in Judgment Aggregation. Proc. COMSOC-2010.

Ulf Endress
52

Computational Social Choice
ECAI-2010

Literature

List (2010) gives a good introduction to the field of JA. Refer to List and Puppe (2009) for additional technical detail.

There are parallels between work in JA and belief merging in AI (cf. Konieczny and Pino Pérez, 2002), which are yet to be fully explored.

C. List, The Theory of Judgment Aggregation: An Introductory Review. *Synthese*. In press (2010).

C. List and C. Puppe, Judgment Aggregation: A Survey. *Handbook of Rational and Social Choice*. Oxford University Press, 2009.

S. Konieczny and R. Pino Pérez, Merging Information under Constraints: A Logical Framework. *Journal of Logic and Computation*, 12(5):773–808, 2002.

52

Computational Social Choice
ECAI-2010

Impossibility Theorem

We have seen that the majority rule is not consistent. Is there a reasonable procedure that is?

Theorem 5 (List and Pettit, 2002) If the agenda contains at least P , Q and $P \wedge Q$, then no aggregation procedure producing consistent and complete judgment sets satisfies both (A) and (S).

C. List and P. Pettit, Aggregating Sets of Judgments: An Impossibility Result. *Economics and Philosophy*, 18(1):89–110, 2002.

Ulf Endress
50

Computational Social Choice
ECAI-2010

Complexity of Judgment Aggregation

There are a number of natural questions arising in JA of which we might want to know their complexity. This is known to date:

- **Safety of the Agenda**: deciding whether an agenda can guarantee consistency for a given class of aggregators (characterised by standard axioms) is typically Π_2^P -complete (worse than NP).
- **Winner Determination**: the complexity of computing the collective judgment set can range from P (*premise-based procedure*) to NP -complete (*distance-based merging*).
- **Manipulation**: in at least one case there is a complexity gap between winner determination and manipulation: manipulation is NP -complete for the *premise-based procedure*.

U. Endress, U. Grandi, and D. Porello, Complexity of Judgment Aggregation: Safety of the Agenda. Proc. AAMAS-2010.

U. Endress, U. Grandi, and D. Porello, Complexity of Winner Determination and Strategic Manipulation in Judgment Aggregation. Proc. COMSOC-2010.

52

Computational Social Choice
ECAI-2010

Fair Division

Fair division is the problem of dividing one or several goods amongst two or more agents in a way that satisfies a suitable fairness criterion. This can be considered a problem of **social choice**:

- A group of agents each have individual preferences over a collective agreement (the allocation of goods to be found).
- But: in fair division preferences are often assumed to be cardinal (*utility functions*) rather than ordinal (as in voting)
 - And: fair division problems come with some *internal structure* often absent from other social choice problems (e.g., I will be indifferent between allocations giving me the same set of goods)

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

Fair Division: Formal Framework

- Let $\mathcal{N} = \{1, \dots, n\}$ be a set of *agents* (or *players*, or *individuals*) who need to share several *goods* (or resources, items, objects).
- An **allocation** A is a mapping of agents to **bundles** of goods.
- Each agent $i \in \mathcal{N}$ has a **utility function** u_i (or **valuation function**), mapping allocations to the reals, to model their preferences.
 - Typically, u_i first defined on bundles, so: $u_i(A) = u_i(A(i))$.
 - Discussion: preference intensity, interpersonal comparison
- An allocation A gives rise to a **utility vector** $(u_1(A), \dots, u_n(A))$.
- Sometimes, we are going to define social preference structures directly over utility vectors $u = \langle u_1, \dots, u_n \rangle$ (elements of \mathbb{R}^n), rather than speaking about the allocations generating them.

Ulf Endriss

57

Computational Social Choice

ECAI-2010

Collective Utility Functions

A **collective utility function** (CUF) is a function $SW : \mathbb{R}^n \rightarrow \mathbb{R}$ mapping utility vectors to the reals. Three important examples:

- the **utilitarian** CUF ranking allocations by total utility

$$SW_{\text{util}}(u) = \sum_{i \in \mathcal{N}} u_i$$

- the **egalitarian** CUF that ties social welfare to the poorest agent

$$SW_{\text{egal}}(u) = \min\{u_i \mid i \in \mathcal{N}\}$$

- the **Nash** CUF that tries to balance fairness and efficiency

$$SW_{\text{nash}}(u) = \prod_{i \in \mathcal{N}} u_i$$

H. Moulin, *Axioms of Cooperative Decision Making*. Econometric Society Monographs, Cambridge University Press, 1988.

Ulf Endriss

59

Computational Social Choice

ECAI-2010

Degrees of Envy

As we cannot always ensure envy-free allocations, another approach would be to try to reduce the **degree of envy** as much as possible.

- Envy between two agents:
 $\max\{u_i(A(j)) - u_i(A(i)), 0\}$ or
 1 if $u_i(A(j)) > u_i(A(i))$ and 0 otherwise
- Degree of envy of a single agent:
 \max, \sum
- Degree of envy of a society:
 \max, \sum [or indeed any CUF]

Y. Chevaleyre, U. Endriss, S. Estivie, and N. Maudet. *Reading Envy-free States in Distributed Negotiation Settings*. Proc. IJCAI-2007.

Ulf Endriss

61

Computational Social Choice

ECAI-2010

Preference Representation Languages

Example: Allocating 10 goods to 5 agents means $5^{10} = 976\,625$ allocations and $2^{10} = 1024$ bundles for each agent to think about. So we need to choose a good **language** to compactly represent preferences over such large numbers of alternative bundles, e.g.:

- Logic-based languages (weighted goals)
- Bidding languages for combinatorial auctions (OR/XOR)
- Program-based preference representation (straight-line programs)
- CP-nets and CI-nets (for ordinal preferences)

The choice of language affects both **algorithm design** and **complexity**.

See Chevaleyre et al. (2008) for references.

Y. Chevaleyre, U. Endriss, J. Lang, and N. Maudet. Preference Handling in Combinatorial Domains: From AI to Social Choice. *AI Magazine*, 29(4):37–46, 2008.

Ulf Endriss

63

Computational Social Choice

ECAI-2010

Complexity Results

Before we look into the “how”, here are some complexity results:

- Checking whether an allocation is **Pareto efficient** is coNP-complete.
- Finding an allocation with maximal **utilitarian** social welfare is NP-hard. If all valuations are **modular** (additive) then it is polynomial.
 - Finding an allocation with maximal **egalitarian** social welfare is also NP-hard, even when all valuations are modular.
 - Checking whether an **envy-free** allocation exists is NP-complete; checking whether an allocation that is both Pareto efficient and envy-free exists is even Σ_2^P -complete.

References to these results may be found in the “MARA Survey”.

Y. Chevaleyre, P.E. Dunne, U. Endriss, J. Lang, M. Lemaître, N. Maudet, J. Padgett, S. Phelps, J.A. Rodríguez-Angulo and P. Sousa. Issues in Multiagent Resource Allocation. *Information*, 30:3–31, 2006.

Ulf Endriss

64

Pareto Efficiency

Allocation A is **Pareto dominated** by allocation A' if $u_i(A) \leq u_i(A')$ for all agents $i \in \mathcal{N}$ and this inequality is strict in at least one case. An allocation A is **Pareto efficient** if there is no other feasible allocation A' such that A is Pareto dominated by A' .

The idea goes back to Vilfredo Pareto (Italian economist, 1848–1923). Discussion:

- Pareto efficiency is very often considered a minimum requirement for any reasonable allocation. It is a very weak criterion.
 - Only the ordinal content of preferences is needed to check Pareto efficiency (no preference intensity, no interpersonal comparison).

Ulf Endriss

58

Computational Social Choice

ECAI-2010

Indivisible Goods: Formal Framework

Fixing goods to be **indivisible** results in a more concrete framework:

- Set of **agents** $\mathcal{N} = \{1, \dots, n\}$ and finite set of indivisible **goods** \mathcal{G} .
- An **allocation** A is a partitioning of \mathcal{G} amongst the agents in \mathcal{N} .
- Example: $A(i) = \{a, b\}$ — agent i owns items a and b
- Each agent $i \in \mathcal{N}$ has got a **valuation function** $v_i : 2^{\mathcal{G}} \rightarrow \mathbb{R}$.
- Example: $v_i(A) = v_i(A(i)) = 577.8$ — agent i is pretty happy
- If agent i receives bundle B and the sum of her payments is x , then her **utility** is $u_i(B, x) = v_i(B) - x$ (“quasi-linear utility”).

For fair division of indivisible goods **without money**, assume that payment balances are always equal to 0 (and utility = valuation).

Ulf Endriss

60

Computational Social Choice

ECAI-2010

Negotiating Socially Optimal Allocations

In AI, one approach has been to design simple *negotiation protocols* allowing agents to make deals regarding the exchange of goods and to analyse the dynamics of those systems.

We can distinguish two perspectives:

- The *local/individual* view: what deals will agents make, given their preferences? Example: myopic rationality
- The *global/social* view: how will the overall allocation evolve in terms of social welfare? Example: utilitarian collective utility

One of the main questions is whether negotiation will *converge* to a social optimum, or under what circumstances it will.

U. Endriss, N. Maudet, F. Sadiq and F. Toni, Negotiating Socially Optimal Allocations of Resources. *Journal of AI Research*, 25:315–348, 2006.

Ulle Endriss

Computational Social Choice

ECAI-2010

Computational Social Choice

ECAI-2010

Cut-and-Choose

The classical approach for dividing a cake between *two agents*:

- One agent *cuts* the cake in two pieces (which she considers to be of equal value), and the other one *chooses* one of the pieces (the piece she prefers).

The cut-and-choose procedure is *proportional*:

- Each agent is guaranteed at least one half (general: $1/n$) according to her own valuation.
- Discussion: In fact, the first agent (if she is risk-averse) will receive exactly $1/2$, while the second will usually get more.

What if there are more than two agents?

Ulle Endriss

ECAI-2010

Computational Social Choice

ECAI-2010

The Even-Paz Divide-and-Conquer Procedure

Even and Paz (1984) investigated *upper bounds* for the number of *queries* (cuts or marks) required for n agents. They introduced the following *divide-and-conquer* protocol:

- (1) Ask each agent to cut the cake at her $\lfloor \frac{n}{2} \rfloor / \lceil \frac{n}{2} \rceil$ mark.
- (2) Associate the union of the leftmost $\lfloor \frac{n}{2} \rfloor$ pieces with the agents who made the leftmost $\lfloor \frac{n}{2} \rfloor$ cuts (group 1), and the rest with the others (group 2).
- (3) Recursively apply the same procedure to each of the two groups, until only a single agent is left. ✓

Each agent is guaranteed a *proportional* piece. Takes $O(n \log n)$ steps.

S. Even and A. Paz, A Note on Cake Cutting. *Discrete Applied Mathematics*, 7:285–296, 1984.

Ulle Endriss

ECAI-2010

Computational Social Choice

ECAI-2010

The Stromquist Procedure

Stromquist (1980) found an envy-free procedure for $n = 3$ producing *contiguous* pieces, though requiring four simultaneously *moving knives*:

- A referee slowly moves a knife across the cake, from left to right (supposed to cut somewhere around the $1/3$ mark).
- At the same time, each agent is moving her own knife so that it would cut the righthand piece in half (wrt. her own valuation).
- The first agent to call “stop” receives the piece to the left of the referee’s knife. The righthand part is cut by the middle one of the three agent knives. If neither of the other two agents hold the middle knife, they each obtain the piece at which their knife is pointing. If one of them does hold the middle knife, then the other one gets the piece at which her knife is pointing. ✓
- W. Stromquist, How to Cut a Cake Fairly. *American Mathematical Monthly*, 87(8):640–644, 1980.

Ulle Endriss

ECAI-2010

Literature


See my lecture notes for a compact introduction to fair division.

Both the book by Brams and Taylor (1996) and that by Robertson and Webb (1998) cover the cake-cutting problem in great depth.

Our JAIR 2006 paper is a possible starting point for finding out more about the problem of fairly allocating indivisible goods.

U. Endriss, *Lecture Notes on Fair Division*. ILLC, University of Amsterdam, 2010.
S.J. Brams and A.D. Taylor, *Fair Division: From Cake-Cutting to Dispute Resolution*. Cambridge University Press, 1996.
J. Robertson and W. Webb, *Cake-Cutting Algorithms: Be Fair if You Can*. A.K. Peters, 1998.
U. Endriss, N. Maudet, F. Sadiq and F. Toni, Negotiating Socially Optimal Allocations of Resources. *Journal of AI Research*, 25:315–348, 2006.

“Cake-cutting” is the problem of fair division of a single *divisible* (and heterogeneous) good between n *agents* (or *players*). The *cake* is represented by the unit interval $[0, 1]$:



Each agent i has a *utility function* u_i (or *valuation, measure*) mapping finite unions of subintervals of $[0, 1]$ to the reals, satisfying:

- Non-negativity: $u_i(B) \geq 0$ for all $B \subseteq [0, 1]$
- Normalisation: $u_i(\emptyset) = 0$ and $u_i([0, 1]) = 1$
- Additivity: $u_i(B \cup B') = u_i(B) + u_i(B')$ for disjoint $B, B' \subseteq [0, 1]$
- u_i is continuous: the Intermediate-Value Theorem applies and single points do not have any value.

Ulle Endriss

Computational Social Choice

ECAI-2010

The Banach-Knaster Last-Diminisher Procedure

In the first ever paper on fair division, Steinhaus (1948) reports on a solution for arbitrary n proposed by Banach and Knaster.

- (1) Agent 1 cuts off a piece (that she considers to represent $1/n$).
- (2) That piece is passed around the agents. Each agent either lets it pass (if she considers it too small) or trims it down further (to what she considers $1/n$).
- (3) After the piece has made the full round, the last agent to cut something off (the “last diminisher”) is obliged to take it.
- (4) The rest (including the trimmings) is then divided amongst the remaining $n-1$ agents. Play cut-and-choose once $n=2$. ✓

Each agent is guaranteed a *proportional* piece. Takes $O(n^2)$ steps.

H. Steinhaus, The Problem of Fair Division. *Econometrica*, 16:101–104, 1948.

Ulle Endriss

Computational Social Choice

ECAI-2010

Envy-Free Procedures

Achieving *envy-freeness* is much harder than achieving proportionality:

- For $n = 2$ the problem is easy: cut-and-choose does the job.
- For $n = 3$ things are already quite complicated: we will see a solution involving *four simultaneously moving knives*.
- For $n = 4$, to date, no procedure producing *contiguous pieces* is known. Brambel and Brams (2004), for example, give a moving-knife procedure requiring up to 5 cuts.
- For $n \geq 6$, to date, only procedures requiring an *unbounded* number of cuts are known (see e.g. Brams and Taylor, 1995). J.B. Barbané and S.J. Brams, Cake Division with Minimal Cuts. *Mathematical Social Sciences*, 48(3):251–269, 2004.
S.J. Brams and A.D. Taylor, An Envy-free Cake Division Protocol. *American Mathematical Monthly*, 102(1):9–18, 1995.

68

Computational Social Choice

ECAI-2010

Ulle Endriss

Computational Social Choice

ECAI-2010

The Stromquist Procedure

Stromquist (1980) found an envy-free procedure for $n = 3$ producing *contiguous* pieces, though requiring four simultaneously *moving knives*:

- A referee slowly moves a knife across the cake, from left to right (supposed to cut somewhere around the $1/3$ mark).
- At the same time, each agent is moving her own knife so that it would cut the righthand piece in half (wrt. her own valuation).
- The first agent to call “stop” receives the piece to the left of the referee’s knife. The righthand part is cut by the middle one of the three agent knives. If neither of the other two agents hold the middle knife, they each obtain the piece at which their knife is pointing. If one of them does hold the middle knife, then the other one gets the piece at which her knife is pointing. ✓
- W. Stromquist, How to Cut a Cake Fairly. *American Mathematical Monthly*, 87(8):640–644, 1980.

Ulle Endriss

ECAI-2010

70

Computational Social Choice

Research can be broadly classified along two dimensions —

The kind of *social choice problem* studied, e.g.:

- electing a winner given individual preferences over candidates
- aggregating individual judgements into a collective verdict
- fairly dividing a cake given individual tastes

The kind of *computational technique* employed, e.g.:

- algorithm design to implement complex mechanisms
- complexity theory to understand limitations
- logical modelling to fully formalise intuitions
- knowledge representation techniques to compactly model problems
- deployment in a multiagent system

Y. Chevaleyre, U. Endriss, J. Lang, and N. Maudet. A Short Introduction to Computational Social Choice. Proc. SOFSEM-2007.

Conclusion

- Tried to give an overview of COMSOC by example, concentrating on preference aggregation, voting, judgment aggregation, and fair division. Omitted e.g., matching and coalition formation.
- Nice topic, particularly for AI people. Still lots to do.
- A website where you can find out more about Computational Social Choice (workshops, mailing list, PhD theses, etc.):
<http://www.ilrc.uva.nl/COMSOC/>
- These slides will remain available on the tutorial website, and more extensive material can be found on the website of my Amsterdam course on Computational Social Choice:
 – <http://www.ilrc.uva.nl/~ulle/teaching/erai-2010/>
 – <http://www.ilrc.uva.nl/~ulle/teaching/comsoc/>